

Description

This mounting tape consists of white, closed-cell polyethylene foam coated on both sides with an aggressive rubber adhesive. It adheres well also onto apolar substrates.

Carrier

Closed-cell polyethylene foam, white, 1000 micron

Liner

White paper, 90 g/m², both sides coated with silicone

Adhesive

Rubber

Area of use

For fixing of boards, displays and for a range of different household applications. A universal and economical product. Also suitable for rough and structured surfaces.

Technical Data

Thickness* (adhesive + foam)	1100 micron	
Density*	58 kg/m ³	
Temperature resistance***	-30° C to +70° C	
Loop Tack* (FINAT TM 9)	37 N/25 mm	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	18 N/25 mm
	after 20 min	> 18 N/25 mm, foam tear
	after 24 h	> 18 N/25 mm, foam tear
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 23°C	> 50 h
	at 70°C	10 min
Temperature resistance * (S.A.F.T.)	70° C	
Shelf life**	1 year	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.

