

Description

This tape consists of a white, closed-cell polyethylene foam coated on both sides with a solvent pure acrylate adhesive. The solvent pure acrylate adhesive guarantees a high final strength and is resistant to extreme temperatures, plasticisers, acids, leaches and solvents. It is inert towards different lacquers for mirrors.

Carrier

Closed-cell polyethylene foam, white, thickness 1.0 mm

Liner

White paper, 140 g/m², both sides coated with silicone and polyethylene

Adhesive

Solvent pure acrylate

Area of use

Used for the installation of mirrors in the furniture and sanitary industry. The recommended amount of applied adhesive area per 1 kg mirror weight is 60 cm². For adhesion of aluminium, steel and GRP outer skins during the construction of truck containers. For the fixing of type and capacity signs as well as displays and product prototypes in the advertising industry. For the fixing of panels and handles in the appliance and electrical industry. Ideal for use in exhibitions, conferences and interior fit-outs. This product provides an excellent bonding performance in the manufacture of solar panels offering long-term exterior adhesion to aluminium and glass panels.

Certificates

This tape is certified according to UL 746C.

Technical Data

Thickness* (adhesive and carrier)	1.1 mm
Density*	67 kg/m ³
Temperature resistance***	-40° C to +95° C
Loop Tack* (FINAT TM 9)	20 N/25 mm
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min: 16 N/25 mm after 20 min: > 16 N/25 mm, foam tear after 24 h: > 16 N/25 mm, foam tear
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 23° C: > 1000 hours at 70° C: > 72 hours
Temperature resistance (S.A.F.T.)	100° C
Shelf life**	2 years
Application temperature	> +18° C

* average ** in original packaging, at 20° C and 50% relative humidity *** normal climate of Central Europe

IMPORTANT NOTICE

All ORAMOUNT® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAMOUNT® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAMOUNT® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAMOUNT® is a registered trademark of ORAFOL Europe GmbH.