

Description

This transfer tape consists of a APEO free modified dispersion acrylate adhesive. This powerful adhesive has high temperature, aging and plasticiser resistance.

Carrier

None

Liner

Siliconized paper, 90 g/m², yellow

Adhesive

APEO free modified dispersion acrylate

Area of use

This tape is suitable for commercial and industrial bonding of textiles, wood, soft PVC and other slightly structured surfaces. Because of its aggressive adhesive it is also appropriate for the adhesion of textiles, wood, open-pore and impregnated foams, cellular polyethylene, soft PVC and other rough, open surfaces.

Technical Data

Thickness* (adhesive without liner)	95 micron	
Temperature resistance***	- 40° C to + 120° C	
Adhesion* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	30 N/25 mm	after 1 min
	35 N/25 mm	after 20 min
	35 N/25 mm	after 24 h
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 24 h	at 23° C
Shelf life**	2 years	
Application temperature	>15° C	

* average ** in original packaging, at 20° C and 50% relative humidity

*** normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH