Description

This double-sided tape consists of a flexible scrim carrier, coated on both sides with an acrylic adhesive. The tape features a very good resistance to ageing and ultraviolet radiation. Due to its high adhesive loading it shows outstanding initial tack and final adhesion, especially to rough and structured surfaces.

Carrier

Rayon (white, translucent)

Liner

Double-sided siliconised paper (90 g/m², yellow)

Adhesive

Modified dispersion acrylic, transparent

Area of use

Mounting of rubber and fotopolymer printing plates or printing blankets in the flexographic printing industry. The high adhesive mass secures a good bonding to mounting films and print cylinders. Suitable as a self-adhesive medium for synthetic profiles and rubber mouldings in commercial and industrial applications.

Technical Data

Thickness* (carrier + adhesive)	380 micron -40° C to +80° C		
Temperature resistance***			
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min: after 20 min: after 24 h:	16 N/25mm 20 N/25mm 25 N/25mm	
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 23° C:	> 6 h	
Shelf life**	2 years		
Application temperature	> +15° C		

^{*} average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORAFLEX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFLEX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFLEX® products and the continuing development of new applications, the purchaser

should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFLEX® is a registered trademark of ORAFOL Europe GmbH.

