## **Application**

Medium hard, one-sided PET carrier foam tape with 500 micron (20 mil) application thickness and differential acrylic adhesives on each side. Enhanced cylinder side adhesion for mounting of thin photopolymer plates up to 1.7 mm (0.067") on print cylinders, composite or urethane sleeves in the flexible packaging and pre-print industry (wide web process).

## Construction

Thickness without liner*	approx. 550 micron (22 mil)
Liner	embossed PP film, 110 micron, white
Adhesive, closed side	Acrylic, low adhesion
Carrier	medium hard PE foam, grey (Orafol Logo) on plate side
Adhesive, open side	acrylic, enhanced adhesion
* average Product Properties	
Medium hard plate mounting tape	
500 micron (20 mil) application thick	ness
Hardness grade "medium" indicated	by the grey colour code
Minimum thickness tolerances	
Differential acrylate with enhanced a	adhesion to cylinder/sleeve for a secure mounting without edge-lifting
Easy and clean demounting	


## **Application fields**

• especially suitable for fine lines, halftones and process printing


Embossed liner enables plate mounting without air entrapments

combination of solid and screen

Easy repositioning







## **IMPORTANT NOTICE**

All ORAFLEX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFLEX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFLEX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFLEX® is a registered trademark of ORAFOL Europe GmbH.

