

## Application

Firm, double coated foam tape with 500 micron (20 mil) application thickness and differential acrylic adhesives on each side. Enhanced cylinder side adhesion for mounting of stiff / thick photopolymer plates on metal print cylinders, composite or urethane sleeves in the flexible packaging and pre-print industry (wide web process).

## Construction

<b>Thickness without liner*</b>	approx. 550 micron (20 mil)
<b>Liner</b>	embossed PP film, 110 micron, white
<b>Adhesive, closed side</b>	acrylic, enhanced adhesion
<b>Carrier</b>	firm PE foam, blue Orafol Logo on plate side
<b>Adhesive, open side</b>	acrylic, enhanced adhesion


\* average

## Product Properties


- firm plate mounting tape
- 500 micron (20 mil) application thickness
- Hardness grade "firm" indicated by the blue colour code
- Minimum thickness tolerances
- Differential acrylate with enhanced adhesion to plate and cylinder / sleeve for a secure mounting without edge-lifting
- Easy and clean demounting
- Easy repositioning
- Embossed liner enables plate mounting without air entrapments

## Application fields

- especially suitable for solids and lines
- dense ink coverage, no pin-holing
- reverse printing



ORAFLEX® 11825  
soft



ORAFLEX® 11855  
medium



ORAFLEX® 11885  
firm

## IMPORTANT NOTICE

All ORAFLEX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFLEX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFLEX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFLEX® is a registered trademark of ORAFOL Europe GmbH.