

ORACAL® BASIC SERIES

Window films for cars

□ □ □ □ □

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

ORACAL®

Basic

[illegible]

ORACAL® □□□□□□□□□□□□

□ □ □ □

PET 0.038

3/3

□□□□□□□□□□

3/3

□□□□□□□□, □□, □□, □□□

□□□□

33

□□□	□□□□□□□□□□
	5 □
□□□	5 □ □ 20 °C □ 50% □□□□□□□□□□
□□□	□□□□ -40 °C
	□□□□ 100 °C

555

1111

□□□□ □□□□ 10 °C

1111

□□□□ 88 %

ORACAL® BASIC SERIES

Window films for cars

UV-A	37 %
UV-B	7.2 %
UV-C	4.9 %
IR	59.7 %
Visible Light	7.9 %
Heat Rejection	32.4 %
Glare Reduction	52 %
Privacy	10.8 %
UV Protection	99 %

ORACAL®

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL®

ORAFOL

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL®
ISO 9001