

ORACAL® BASIC SERIES

Window films for cars

□ □ □ □ □

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

ORACAL®

Basic

[illegible]

ORACAL® □□□□□□□□□□□□

□ □ □ □

PET, 0.038

333

□□□□□□□□□□

3/3

□□□□□□□□, □□, □□, □□

□□□□

100

□□□	□□□□□□□□□□	
	5 □	
□□□	5 □	□ 20 °C □ 50% □□□□□□□□□□
□□□	□□□□ -40 °C	
	□□□□ 100 °C	

□□□□□

4444

□□□□ □□□□ 10 °C

444

□□□□ 55 %

ORACAL® BASIC SERIES

Window films for cars

UV-A	37 %
UV-B	8.1 %
UV-C	7.3 %
IR	44.3 %
Visible Light	9.3 %
Heat Rejection	46.4 %
Glare Reduction	42 %
Sound Reduction	40.5 %
UV Protection	99 %

ORACAL®

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL®

ORACAL®

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL®

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORAFOL is a registered trademark of ORAFOL Europe GmbH.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

ORACAL®
ISO 9001