

ORAJET® 3162HOP

High Opacity Film

□ □ □ □ □

□□□ PVC□□□□□□□□□□ >99%

ORAJET®3162

□ □ □ □

□□ PVC□□ , 0.1 □□

333

□□□□□□□□ , 137 g / m²

10/10

00000 , 000 , 00 , 0.019 %

□ □ □ □

333

□□□	4 □	□□□
□□□	2 □	□ 20 °C □ 50% □□□□□□□□□□
□□□□	□□□□ 1 □ □□□□ 1 □	Verklebt auf Aluminium FINAT TM 14, Durchschnittswert
□□□□□	□□□□□□□ 130 % □□□□□□□ 150 %	DIN EN ISO 527
□□□□	□□□□□□□ 19 N /□□□□ □□□□□□□ 19 N /□□□□	DIN EN ISO 527 □□
□□□	□□□□ -40 °C □□□□ 60 °C	□□□□□□ 80°C□□□

□ □ □ □ □

6 N / 2500 FINAT TM 1, 24h | Finat TM 10000

ORAJET® 3162HOP

High Opacity Film

444

4/4

10 °C

□□□□

1111

10 °C

□ □ □ □

[illegible]

□ □ □ □ □





000

[illegible]

ORAFOL

ORAJET® □ ORAFOL Europe GmbH □□□□□

OAJET®
OAJET®