

ORACAL® 1050

High Performance Vinyl

000000

000 PVC0000000000000000

00000

000 PVC00 , 0.1 00

000

0000000 , 137 g / m²

000

0000000 , 00 , 00 , 0.025 00

00000

000

000

0000000000000000

7 0

000

2 0

0 20 °C 0 50% 00000000000000

00000000

00 , 00 , 00 , 00 , 000 , 000 ,
0000 0.5%000000

000

0000

00000 0.2 00
00000 0 00

0000 | FINAT TM 14

00000

00000000 130 %
00000000 150 %

DIN EN ISO 527

0000

00000000 19 N /0000
00000000 19 N /0000

DIN EN ISO 527

0000

0000

100 000 /35°C | 00000000

DIN EN ISO 9227 00

000

0000 -40 °C
0000 60 °C

000000000000

ORACAL® 1050

High Performance Vinyl

□ □ □ □ □

33

20 N / 25□□

24000000

| FINAT TM 1

□□□□

□□□□

□□□□ 10 °C

□□□□

[illegible]

5/5/2014

[illegible]

□□□□□□□□□□□□□□□□□□□□

ORACAL® □□□□□□□□□□□□□□□□□□□□□□

ORACAL® □□□

ORAFOL

ORACAL® □ ORAFOL Europe GmbH □□□□□

ORACAL®
ISO 9001