

ORACAL® 1630

Print Vinyl

000000

000 PVC000000000000000000

*000000

00000

00 PVC00 , 0.1 00

000

00000000 , 137 g / m²

000

00000000 , 000 , 00 , 0.023 00

00000

000

000	000000000000000000		
	3 0		
000	2 0		
	0 20 °C 50% 0000000000000000		
0000	00000	0.4 00	00000 FINAT TM 14
	00000	0 00	FINAT TM 14
00000	00000000	130 %	DIN EN ISO 527
	00000000	150 %	
0000	00000000	19 N / 0000	DIN EN ISO 527
	00000000	19 N / 0000	
0000	0000		100 000 /35°C 00000000 DIN EN ISO 9227 00
000	0000	-40 °C	000000000000
	0000	60 °C	

000000

000	5 N / 2500	2400000000	FINAT TM 1
-----	------------	------------	------------

ORACAL® 1630

Print Vinyl

444

□□□□

□□□□ 10 °C

□□□□

[illegible]

□ □ □ □ □

[illegible]

□□□□□□□□□□□□□□□□□□□□

ORACAL® □□□□□□□□□□□□□□□□□□□□□□

ORACAL® □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

ORAFOL

ORACAL® □ ORAFOL Europe GmbH □□□□□

ORACAL®
ISO 9001