

ORACAL® 1650

Print Vinyl

000000

000 PVC0000000000000000

*000000

00000

00 PVC00 , 0.1 00

000

00000000 , 137 g / m²

000

00000000 , 00 , 00 , 0.023 00

00000

000

000

0000000000000000

3 0

000

2 0

0 20 °C 0 50% 0000000000000000

0000

00000 0.4 00
00000 0 00

00000 | FINAT TM 14
FINAT TM 14

00000

00000000 130 %
00000000 150 %

DIN EN ISO 527

0000

00000000 19 N / 0000
00000000 19 N / 0000

DIN EN ISO 527

0000

0000

100 000 /35°C | 00000000

DIN EN ISO 9227 00

000

0000 -40 °C
0000 60 °C

00000000000000

000000

000

18 N / 2500

2400000000

| 0000

FINAT TM 1

ORACAL® 1650

Print Vinyl

1111

□□□□

□□□□ 10 °C

□□□□

[illegible]

□□□□□

[illegible]

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

ORACAL® □□□□□□□□□□□□□□□□□□□□□□

ORACAL®

ORAFOL

ORACAL® □ ORAFOL Europe GmbH □□□□□

ORACAL®
ISO 9001