

ORACAL® 383
Ultraleaf Cast

□ □ □ □ □

[illegible]

Ultraleaf

Cast

[illegible]

□ □ □ □

□□□□, 0.085 □□

11/11

□□□□□□□□ , 137 g / m²

100

□□□□□□□□ , □□ , □□ , 0.03 □□

□ □ □ □ □ □

ORATAPE® HT95 Application Tape, ORATAPE® LT52 Application Tape, ORATAPE® LT95 Application Tape, ORATAPE® MT52 Application Tape, ORATAPE® MT72 Application Tape, ORATAPE® MT80P Application Tape, ORATAPE® MT95 Application Tape

□ □ □ □

111

□□□	□□□□□□□□□□	
	5 □	□□□□□□□□□□□□□□□□□□
□□□	2 □	□ 20 °C □ 50% □□□□□□□□□□
□□□□□□	□□ , □□ , □□ , □□ , □□□ , □□□ , □□□□ □□□□ 0.5%□□□□□□	□□□
□□□□	□□□□ 0.25 □□ □□□□ 0.25 □□	verklebt auf Aluminium FINAT TM 14, Durchschnittswert
□□□□□	□□□□□□□□ 35 % □□□□□□□□ 35 %	DIN EN ISO 527
□□□□	□□□□□□□□ 17 N /□□□□ □□□□□□□□ 17 N /□□□□	DIN EN ISO 527

ORACAL® 383
Ultraleaf Cast

333

□□□□	-40 °C
□□□□	60 °C

10/10/10

□□□□□

333

16 N / 25□□

24□□□□□□□□

| 0000 FINAT TM 1

□□□□

4/4

□□□□ 10 °C

□□□□

[illegible]

5/5/2019

ISO ORACAL® 9001

[illegible][illegible]

ORAFOL

ORACAL® □ ORAFOL Europe GmbH □□□□□

ORACAL®
ORACAL®