

ORACAL® 551

High Performance Cal

□ □ □ □ □

☐ PVC

□ □ □ □

□□□ PVC□□ , 0.07 □□

100

□□□□□□□□ , 137 g / m²

10/10

00000000 , 00 , 00 , 0.024 00

□ □ □ □ □ □

ORATAPE® HT95 Application Tape, ORATAPE® LT52 Application Tape, ORATAPE® LT95 Application Tape, ORATAPE® MT52 Application Tape, ORATAPE® MT72 Application Tape, ORATAPE® MT80P Application Tape, ORATAPE® MT95 Application Tape

1111

333

□□□	□□□□□□□□□□	
8 □	□□□□□□□□□□□□□□□□□□□□□□□□	
7 □	□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□	case
4 □	□□□□□□□□□□□□□□□□□□□□□□□□	
3 □	Brilliant blue L □□□□□□□□□□□□□□□□□□□□□□□□	
2 □	□ 20 °C □ 50% □□□□□□□□□□□□	
□□□□□□	□□ , □□ , □□ , □□□ , □□ , □□□ □□□ , □□□□ 0.5% □□□□□□	
□□□□	□□□□ 0.2 □□ □□□□ 0 □□	□□□□ FINAT TM 14 FINAT TM 14

ORACAL® 551

High Performance Cal

□□□□□	□□□□□□□□ □□□□□□□	150 % 170 %	DIN EN ISO 527
□□□□	□□□□□□□ □□□□ □□□□□□□□ □□□□	19 N / 19 N /	DIN EN ISO 527
□□□□	□□□□	100 □□□ /35°C □□□□□□□	DIN EN ISO 9227 □□
□□□	□□□□ □□□□	-40 °C 60 °C	□□□□□□□□□□□□

□□□□□

18 N / 2500 240000000 | 0000 FINAT TM 1

□□□□

□□□□ □□□□ 10 °C



- ABG_551_D5291.pdf (Download)
- ABG_551_D5291.pdf (Download)
- ABG_551_D5291.pdf (Download)
- ABG_551_D5291.pdf (Download)
- ABG_551_D5291.pdf (Download)
- ABG_551_D5291.pdf (Download)

□ □ □ □

[illegible]

ORACAL® 551

High Performance Cal

□ □ □ □ □

[illegible]

□□□□□□□□□□□□□□□□□□□□

ORACAL® □□□□□□□□□□□□□□□□□□□□□□

ORACAL®

[illegible]

ORAFOL

ORACAL® □ ORAFOL Europe GmbH □□□□□

ORACAL®
ISO 9001