

ORACAL® 640

Print Vinyl

□ □ □ □ □

☐ PVC

□ □ □ □

□□ PVC□□ , 0.08 □□

□□□

□□□□□□□□ , 137 g / m²

10/10

00000 , 00 , 00 , 0.019 00

□□□□

111

□□□	□□□□□□□□□□	
	3 □	□□□□□□□□□□□□□□□□□□
□□□	2 □	□ 20 °C □ 50% □□□□□□□□□□
□□□□	□□□□ 0.4 □□ □□□□ 0 □□	□□□□ FINAT TM 14
□□□□□	□□□□□□ 130 % □□□□□□ 150 %	DIN EN ISO 527
□□□□	□□□□□□ 19 N /□□□□ □□□□□□ 19 N /□□□□	DIN EN ISO 527
□□□	□□□□ -40 °C □□□□ 60 °C	□□□□□□□□□□

5/5/2014

16 N / 2500 240000000 | 0000 FINAT TM 1

1111

□□□□ □□□□ 10 °C

ORACAL® 640

Print Vinyl



- ABG_640_D5426.pdf (Download)
- 640G-010 Test Certificate BS 5609.pdf (Download)
- ABG_640_D5426.pdf (Download)
- 640G-010 Test Certificate BS 5609.pdf (Download)
- ABG_640_D5426.pdf (Download)
- 640G-010 Test Certificate BS 5609.pdf (Download)
- ABG_640_D5426.pdf (Download)
- 640G-010 Test Certificate BS 5609.pdf (Download)
- ABG_640_D5426.pdf (Download)
- 640G-010 Test Certificate BS 5609.pdf (Download)
- ABG_640_D5426.pdf (Download)

[illegible]

ORACAL® 日本製
ISO 9001 品質保証
品質保証
品質保証
品質保証
ORAFOL Europe GmbH 日本製

ORACAL®
ORACAL®
ORAFOL
ORACAL® □