

ORACAL® 6510

Fluorescent Cast

□ □ □ □ □

□□□	PVC
-----	-----

[illegible]

□□□□

□□ PVC□□ , □□ , 0.11 □□

111

□□□□□□□□ , 137 g / m²

100

00000000 , 00 , 00 , 0.027 00

□ □ □ □ □ □

ORATAPE® HT95 Application Tape, ORATAPE® LT52 Application Tape, ORATAPE® LT95 Application Tape, ORATAPE® MT52 Application Tape, ORATAPE® MT72 Application Tape, ORATAPE® MT80P Application Tape, ORATAPE® MT95 Application Tape

□ □ □ □

10/10

□ □ □	□ □ □ □ □ □ □ □ □ □ □ □		
	1 □	□ □ □ □ □ □ □ □	
	2 □	□ □ □ □ □ □ □	
□ □ □	2 □	□ 20 °C □ 50% □ □ □ □ □ □ □ □ □ □ □ □	
□ □ □ □	□ □ □ □ □ 0.3 □ □ □ □ □ □ □ 0 □ □	□ □ □ □ □ FINAT TM 14	
□ □ □ □ □	□ □ □ □ □ □ □ □ 100 % □ □ □ □ □ □ □ □ 199 %	DIN EN ISO 527	
□ □ □ □	□ □ □ □ □ □ □ 13 N / □ □ □ □ □ □ □ □ □ □ □ □ 13 N / □ □ □ □	DIN EN ISO 527	

ORACAL® 6510

Fluorescent Cast

□□□□	□□□□	100 □□□ /35°C □□□□□□	DIN EN ISO 9227 □□
□□□	□□□□ □□□□	-40 °C 60 °C	□□□□□□□□□□

□□□□□

16 N / 2500 240000000 | FINAT TM 1

4444

□□□□ □□□□ 10 °C

□□□□

[illegible]

□ □ □ □ □

11

000

☐ ☐

ORACAL®

ORACAL® □□□

ORAFOL

ORACAL® □ ORAFOL Europe GmbH □□□□□

ORACAL®
ISO 9001