

ORACAL® 8510RA

Etched Glass Cal

□ □ □ □ □

PVC

□ □ □ □

□□□ PVC□□ , 0.08 □□

11/11

PE RaidAir, 143 g / m²

333

□□□□□□□□ , □□ , □□ , 0.03 □□

□ □ □ □ □ □

ORATAPE® HT95 Application Tape, ORATAPE® LT52 Application Tape, ORATAPE® MT95 Application Tape, ORATAPE® LT95 Application Tape, ORATAPE® MT52 Application Tape, ORATAPE® MT72 Application Tape, ORATAPE® MT80P Application Tape

□ □ □ □

333

□□□	□□□□□□□□□□	
	7 □	
□□□	2 □	□ 20 °C □ 50% □□□□□□□□□□
□□□□□□	□□ , □□ , □□ , □□ , □□□ , □□□ , □□□□ □□□□ 0.5%□□□□□	□□□
□□□□	□□□□ 0.2 □□ □□□□ 0 □□	□□□□ FINAT™ 14
□□□□□	□□□□□□□ 130 % □□□□□□□ 150 %	DIN EN ISO 527
□□□□	□□□□□□□ 19 N /□□□□ □□□□□□□ 19 N /□□□□	DIN EN ISO 527

ORACAL® 8510RA
Etched Glass Cal

333

□□□□	-40 °C
□□□□	60 °C

11111111

□□□□□

333

18 N / 25□□

000 24000 | 0000 FINAT TM 1

16 N / 25□□

0000 24000 | 0000 FINAT TM 1

□□□□

444

□□□□ 10 °C

□ □ □ □

[illegible]

□ □ □ □ □

11

000

[illegible]

ORACAL®

ORACAL®

[illegible]

ORAFOL

ORACAL® □ ORAFOL Europe GmbH □□□□□

ORACAL®
ISO 9001