

ORACAL® 8800

Translucent Premium Cast

□ □ □ □ □

[illegible]

□□□□

□□ PVC□□ , □□ , 0.05 □□

333

, 0.1

111

□□□□□□□□ , □□ , □□ , 0.03 □□

□ □ □ □ □ □

ORATAPE® HT95 Application Tape, ORATAPE® LT52 Application Tape, ORATAPE® MT95 Application Tape, ORATAPE® LT95 Application Tape, ORATAPE® MT52 Application Tape, ORATAPE® MT72 Application Tape, ORATAPE® MT80P Application Tape

□ □ □ □

333

□□□	□□□□□□□□□□	
	10 □	□□□□
	8 □	□□
	5 □	□□
□□□	2 □	□ 20 °C □ 50% □□□□□□□□□□
□□□□	□□□□ 0.1 □□ □□□□ 0.1 □□	□□□□ FINAT TM 14, Durchschnittswert
□□□□□	□□□□□□□ 120 % □□□□□□□ 120 %	DIN EN ISO 527
□□□□	□□□□□□□ 21 N /□□□□ □□□□□□□ 21 N /□□□□	DIN EN ISO 527

ORACAL® 8800

Translucent Premium Cast

333

□□□□	-40 °C
□□□□	60 °C

10/10/10

□□□□□

33

18 N / 25□□

000000 24000 | 0000 FINAT TM 1

16 N / 25□□

00000000 24000 | 0000 FINAT TM 1

□□□□

444

□□□□ 10 °C

□□□□

[illegible]

□ □ □ □ □

11

000

[illegible]

ORACAL® □□□□□□□□□□□□□□□□□□□□□□□□□□□□

ORACAL®

[illegible]

ORAFOL

ORACAL® □ ORAFOL Europe GmbH □□□□□

ORACAL®
ISO 9001