

ORACAL® 970RA

Premium Wrapping Cast

5/5

□□□□□□□□□□

[illegible]

RapidAir®

[illegible]

PVC

□□□□

□□ PVC□□ , □□ , 0.11 □□



PE RaidAir, 143 g / m²

10/10

□□□□□□□□ , □□ , □□ , □□□ , 0.03 □□

□□□□

11/11

[illegible]

ORACAL® 970RA
Premium Wrapping Cast

0000000 00 , 00 , 00 , 00 ,
000 , 000 , 0000
0.5%000000

000

0000 00000 0.1 00 00000 | FINAT TM 14
00000 0 00

00000 00000000 150 % DIN EN ISO 527
00000000 150 %

00000000 120 % 000 DIN EN ISO 527
00000000 120 %

00000000 35 % Structure, DIN EN ISO 527
00000000 35 %

0000 00000000 21 N / DIN EN ISO 527
0000
0000000000 21 N /
0000

0000 0000 100 000 /35°C | 00000000 DIN EN ISO 9227 00

000 0000 -40 °C 0000000000
0000 60 °C

00000

000 16 N / 2500 24h0000 | FINAT TM 10000

0000

0000 0000 10 °C

ORACAL® 970RA

Premium Wrapping Cast



- [970GRA-010 Test Certificate BS5609 Section 2.pdf](#) (Download)
- [970GRA-010 Test Certificate BS5609 Section 2.pdf](#) (Download)
- [970GRA-010 Test Certificate BS5609 Section 2.pdf](#) (Download)
- [970GRA-010 Test Certificate BS5609 Section 2.pdf](#) (Download)
- [970GRA-010 Test Certificate BS5609 Section 2.pdf](#) (Download)
- [970GRA-010 Test Certificate BS5609 Section 2.pdf](#) (Download)
- [ORACAL 970RA DIN EN 45545-2.pdf](#) (Download)
- [ORACAL 970RA DIN EN 45545-2.pdf](#) (Download)

[illegible]

ORACAL®
ORA-FOL
ORACAL® ORA-FOL Europe GmbH

ORACAL®
ISO 9001