

ORACAL® SAFETY
Safety Window Film

□ □ □ □ □

□□□□□□

[illegible]

PET

□□□□

PET, 0.1

333

□□□□□□□□□□

1111

□□□□□□□□, □□, □□

□ □ □ □

333

111

□□□□□□□□□□

50

11/11

20

□ 20 °C □ 50% □□□□□□□□□□□□

11/11

000000

151

□□□□□□□□

151

11

1111

-40 °C

1111

100 °C

□ □ □ □ □

111

4.5 N-10mm

24□□□□□□

| Finat TM 10000

□□□□

1111

1111

10 °C

□ □ □ □ □ □

1111

ORACAL® SAFETY

Safety Window Film

Table 1

UV-A	100 %
UV-B	8 %
UV-C	9 %
UV-D	7 %
UV-E	84 %
UV-F	16.8 %
UV-G	88.9 %
UV-H	99 %

Table 2

Table 2: Additional technical specifications and performance data for the Safety Window Film.

Table 3

Table 3: Additional technical specifications and performance data for the Safety Window Film.

ORACAL® SAFETY is a registered trademark of ORAFOL Europe GmbH.

ORAFOL is a registered trademark of ORAFOL Europe GmbH.

ORACAL® SAFETY is a registered trademark of ORAFOL Europe GmbH.

ORACAL®
ISO 9001