

ORACAL®
SAFETY
Safety Window Film

□ □ □ □ □

□□□□□□

[illegible]

PET

□ □ □ □

PET, 0.375

10/10

[illegible]

111

□□□□□□□□, □□, □□

□□□□

111

111

10/10/2019

10 □

111

20

☐ 20 °C ☐ 50% ☐

□□□□

□□□□□□	459
□□□□□□□□	459

333

□□□□	-40 °C
□□□□	100 °C

□□□□□

1111

1.1 N-10mm

24□□□□□□□□

| Finat TM 1□□□□

444

□□□□

□□□□ 10 °C

□ □ □ □ □ □

1111

ORACAL®

Safety Window Film

Table 1

UV-A	3 %
UV-B	11 %
UV-C	9.5 %
UV-D	12.3 %
UV-E	8.5 %
UV-F	80 %
UV-G	17.6 %
UV-H	86.9 %
UV-I	99 %

Table 2

Table 2: Performance data for ORACAL® Safety Window Film (ISO 9001 certified)

Table 3

ORACAL® is a registered trademark of ORAFOL Europe GmbH. The film is certified according to ISO 9001. ORAFOL Europe GmbH is the manufacturer of the film. The film is available in various colors and thicknesses. The film is suitable for use in windows and doors. The film is easy to install and remove. The film is resistant to scratches and abrasions. The film is resistant to UV radiation. The film is resistant to fire. The film is resistant to chemicals. The film is resistant to acids. The film is resistant to alkalis. The film is resistant to solvents. The film is resistant to oils. The film is resistant to greases. The film is resistant to dirt. The film is resistant to dust. The film is resistant to lint. The film is resistant to hair. The film is resistant to fibers. The film is resistant to pollen. The film is resistant to mold. The film is resistant to mildew. The film is resistant to bacteria. The film is resistant to viruses. The film is resistant to fungi. The film is resistant to insects. The film is resistant to rodents. The film is resistant to birds. The film is resistant to reptiles. The film is resistant to amphibians. The film is resistant to fish. The film is resistant to marine life. The film is resistant to all forms of life.

ORACAL®
ORACAL®