

ORAGUARD® 215

Laminating Film

000000

000 PVC000000000000000000000000

000000

000 PVC000 , 0.075

0000

00000000 , 90 g / m²

0000

00000000 , 00 , 00 , 0.024

000000

000

000

0000000000000000

5

000

2

20 °C 50% 0000000000000000

00000000

0 , 00 , 000 , 000 , 0000 0.5% 000

0000

00000 0.2
00000 0.3

0000 | FINAT TM 140000

000000

00000000 130 %
00000000 150 %

DIN EN ISO 527

0000

00000000 19 N /
00000000 19 N /

DIN EN ISO 527

0000

0000 -40 °C
0000 60 °C

00000000

000000

000

12 N / 25

2400000000000000

| FINAT TM 1

ORAGUARD® 215

Laminating Film

□ □ □ □

□□□□

□□□□ 10 °C

22

- 3554 - 215_C-s1,d0_Klassifizierung nach DIN EN 13501-1.pdf (Download)
- 3554 - 215_C-s1,d0_Klassifizierung nach DIN EN 13501-1.pdf (Download)

□ □ □ □

[illegible]

ORAGUARD®

□ □ □ □ □

ORAGUARD®

ORAGUARD®
ISO 9001

ORAGUARD®
ORAFOL