

ORAGUARD® 255AS

Laminating Film

000000

0000 PVC 000000000000

0000

00 PVC 00 , 0.017 00

000

00000000 , 90 g / m²

000

00000000 , 00 , 00 , 0.024 00

0000

000

000

000000000000

2 0

000000000000000000000000

5 0

000000000000000000000000000000

1 0

000000000000000000000000 | < 100000 / 00000000

000

2 0

0 20 °C 0 50% 0000000000000000

00000000

00 , 000 , 0 , 000 , 0000 0.5% 000000

000

0000

000000 0.4 00
000000 0.4 00

verklebt auf Aluminium | FINAT TM 14, Durchschnittswert

000000

00000000 130 %
00000000 150 %

DIN EN ISO 527

0000

00000000 22 N / 0000
00000000 22 N / 0000

DIN EN ISO 527 00

000

0000 -40 °C
0000 60 °C

0000000000



ORAGUARD® 255AS

Laminating Film

□ □ □ □ □

333

12 N / 25□□

24□□□□□□□□□□□□□□

| 000

□□□□

□□□□

□□□□ 10 °C

□ □ □ □

[illegible]

ORAGUARD®

5/5/2014

ORAGUARD®

ORAGUARD®
ISO 9001

ORAGUARD®
ORAFOL