

ORAGUARD® 373
Anti-Graffiti Film

□ □ □ □ □

[illegible]

UV

□ □ □ □

PET, 0.025

100

PE	155 g / m ²
----	------------------------

10/10

□□□□□□□□ , □□ , □□ , 0.024 □□

□□□□

333

□□□	□□□□□□□□□□□□	
	5 □	
□□□	2 □	□ 20 °C □ 50% □□□□□□□□□□□□
□□□□□□□	□□ , □□□ , □ , □□□ , □□□□ 0.5%	□□□
	□□□□□□	
□□□□	□□□□ 0.2 □□ □□□□ 0.2 □□	verklebt auf Aluminium FINAT TM 14 FINAT TM 14
□□□□	□□□□	100 □□□ /35°C □□□□□□□□ DIN EN ISO 9227 □□
□□□	□□□□ -40 °C □□□□ 100 °C	

□□□□□

12 N / 2500 2400000000 | FINAT TM 10000

1111

□□□□ □□□□ 10 °C

ORAGUARD® 373
Anti-Graffiti Film



- [Orajet3951GRA_Oraguard244_DIN_EN_45545_L1_2_3-R17.pdf](#) (Download)
- [Orajet3951GRA_Oraguard244_DIN_EN_45545_L1_2_3-R17.pdf](#) (Download)

[illegible]

ORAGUARD®

ORAGUARD®
ISO 9001

ORAGUARD®
ORAFOL