

ORAJET® 3162
Digital Printing Film

000000

00 PVC 000000000000000000000000

00000

00 PVC00 , 0.1 00

000

00000000 , 137 g / m²

000

00000 , 000 , 00 , 0.019 00

00000

000

000	000000000000000000000000		
	4 0		000000000000000000000000
000	2 0		0 20 °C 50% 0000000000000000
0000	0000 0.4 00 0000 0 00		FINAT TM 14000000 FINAT TM 14, Durchschnittswert
00000	00000000 130 % 00000000 150 %		DIN EN ISO 527
0000	00000000 19 N /0000 00000000 19 N /0000		DIN EN ISO 527
000	0000 -40 °C 0000 60 °C		0000000000000000

00000

000	6 N / 2500	2400000000	FINAT TM 10000
-----	------------	------------	----------------

0000

0000	0000 10 °C		
------	------------	--	--



ORAJET® 3162

Digital Printing Film



- [3162_3162X-010_B-s2_d0-mineralischer_Untergrund_Klassifizierung_DIN_EN_13501-1_de.pdf](#) (Download)
- [3162_3162X-010_B-s2_d0-mineral_substrate_classification_acc_DIN_EN_13501-1_en.pdf](#) (Download)

[illegible]

ISO 9001
ORAJET® ORAFOL Europe GmbH

ORAJET®
ORAJET®