

ORAJET® 3164

Digital Printing Film

□ □ □ □ □

11

PVC

□ □ □ □

□□ PVC□□ , 0.1 □□

333

□□□□□□ , 137 g / m²

3/3

00000 , 00 , 00 , 0.019 00

□ □ □ □

333

□□□	□□□□□□□□□□	
	4 □	□□□□□□□□□□□□□□
□□□	2 □	□ 20 °C □ 50% □□□□□□□□□□
□□□□	□□□□ 0.4 □□ □□□□ 0 □□	□□□□ FINAT TM 14
□□□□□	□□□□□□□ 130 % □□□□□□□ 150 %	DIN EN ISO 527
□□□□	□□□□□□□ 19 N /□□□□ □□□□□□□ 19 N /□□□□	DIN EN ISO 527
□□□	□□□□ -40 °C □□□□ 60 °C	□□□□

5/5/2014

16 N / 2500 2400000000 | FINAT TM 1

□□□□

□□□□ □□□□ 10 °C

ORAJET® 3164

Digital Printing Film



- [3164_3164X_3164XRA_B-s1,d0_metallischer Untergrund - Klassifizierung nach DIN EN 13501-1 - de.pdf](#)
(Download)
- [3164_3164X_3164XRA_B-s1,d0_metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#)
(Download)
- [3164_3164X_3164XRA_B-s1,d0_metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#)
(Download)
- [3164_3164X_3164XRA_B-s1,d0_metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#)
(Download)
- [3164_3164X_3164XRA_B-s1,d0_metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#)
(Download)
- [3164_3164X_3164XRA_B-s1,d0_metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#)
(Download)

[illegible]

ISO 9001

ORAFOL®
ORAFOL Europe GmbH

ORAJET®
ORAJET®