

ORAJET® 3165RA

Digital Printing Film

□ □ □ □ □

□□□□□□	PVC
--------	-----

[illegible]

RapidAir □□□□□□□□□□

□ □ □ □

□□□□ PVC□□ , 0.1 □□

333

PE RaidAir, 143 g / m²

3/3

□□□□□□□□ , □□ , □□□□□□ , 0.03 □□

□□□□

ORAGUARD® 213

□ □ □ □

11/11

□□□	□□□□□□□□□□	
	5 □	□□□□□□□□□□□□□□□□□□
□□□	2 □	□ 20 °C □ 50% □□□□□□□□□□
□□□□	□□□□ 0.4 □□ □□□□ 0 □□	Verklebt auf Aluminium FINAT TM 14, Durchschnittswert
□□□□□	□□□□□□□ 130 % □□□□□□□ 150 %	DIN EN ISO 527
□□□□	□□□□□□□ 19 N /□□□□ □□□□□□□ 19 N /□□□□	DIN EN ISO 527 □□
□□□	□□□□ -40 °C □□□□ 60 °C	□□□□□□ 80°C□□□

5/5

16 N / 2500 24000000 | 0000 FINAT TM 1

ORAJET® 3165RA

Digital Printing Film

4/4

4444

□□□□ 10 °C

11

- [3165_3165RA 010 - 215_C-s2,d0 - metallischer Untergrund - Klassifizierung nach DIN EN 13501-1 - de.pdf](#) (Download)
- [3165_3165RA 010 - 215_C-s2,d0 - metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3165_3165RA 010 - 215_C-s2,d0 - metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3165_3165RA 010 - 215_C-s2,d0 - metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3165_3165RA 010 - 215_C-s2,d0 - metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3165_3165RA 010 - 215_C-s2,d0 - metallic substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)

11/11

Copyright © 2015 Pearson Education, Inc. or its affiliate(s). All rights reserved.

5/5/2019

ISO 9001

ORAJET®

ORAJOL

ORAJET®

ORAJOL Europe GmbH

ORAJET®
ORAJET®