

ORAJET® 3172X
Digital Printing Film

000000

0 PVC000000000000000000000000

00000

PP00 , 0.1 00

000

0000000 , 137 g / m²

000

00000 , 000 , 00 , 0.02 00

00000

000

000

0000000000000000

2 0

000000000000000000

000

2 0

0 20 °C 0 50% 00000000000000

0000

00000 0.3 00
00000 0 00

0000 | FINAT TM 14

00000

00000000 400 %
00000000 450 %

DIN EN ISO 527

0000

00000000 15 N / 0000
00000000 15 N / 0000

DIN EN ISO 527

000

0000 -40 °C
0000 100 °C

00000

000

2 N / 2500

2400000000

| FINAT TM 10000

0000

0000

0000 10 °C



ORAJET® 3172X

Digital Printing Film



- 3172X__236_C-s1_d0-mineral.Untergrund_DIN_13501-1_de.pdf (Download)
- 3172X B-s1_d0 - Klassifizierung nach DIN EN 13501-1.pdf (Download)
- 3172X__236_C-s1_d0-mineral_substrate_DIN_13501-1_en.pdf (Download)
- 3172X B-s1_d0 - Klassifizierung nach DIN EN 13501-1 engl.pdf (Download)
- 3172X__236_C-s1_d0-mineral_substrate_DIN_13501-1_en.pdf (Download)
- 3172X B-s1_d0 - Klassifizierung nach DIN EN 13501-1 engl.pdf (Download)
- 3172X__236_C-s1_d0-mineral_substrate_DIN_13501-1_en.pdf (Download)
- 3172X B-s1_d0 - Klassifizierung nach DIN EN 13501-1 engl.pdf (Download)
- 3172X B-s1_d0 - Klassifizierung nach DIN EN 13501-1 engl.pdf (Download)
- 3172X__236_C-s1_d0-mineral_substrate_DIN_13501-1_en.pdf (Download)
- 3172X B-s1_d0 - Klassifizierung nach DIN EN 13501-1 engl.pdf (Download)
- 3172X__236_C-s1_d0-mineral_substrate_DIN_13501-1_en.pdf (Download)

[illegible]

ORAJET® 9001
ISO 9001
ORAFOL
ORAJET® ORAFOL Europe GmbH

ORAJET®
ORAJET®