

ORAJET® 3550

Digital Printing Film

000000

000 PVC00000000

00000

000 PVC00 , 0.07 00

000

00 PE00000000000 , 143 g / m²

000

0000000 , 00 , 00 , 000 , 0.026 00

00000

ORAGUARD® XP279

00000

000

000	00000000000000		
	7 0	000000000000000000	
000	2 0	0 20 °C 50% 00000000000000	
00000000	00 , 00 , 00 , 00 , 000 , 000 , 0000 0.5%000000	000	
0000	0000 0.2 00 0000 0 00	0000 FINAT TM 14 0000	
00000	00000000 130 % 00000000 150 %	DIN EN ISO 527	
0000	00000000 19 N /0000 00000000 19 N /0000	DIN EN ISO 527	
0000	0000	100 000 /35°C 00000000	DIN EN ISO 9227 00



ORAJET® 3550

Digital Printing Film

333

□□□□	-40 °C
□□□□	60 °C

10/10/10

□□□□□

333

18 N / 25□□

24□□□□□□

| FINAT™ 10000

□ □ □ □

11/11

□□□□ 10 °C

□□□□

[illegible]

5/5/2014





[illegible][illegible]

ORAFOL

ORAJET® □ ORAFOL Europe GmbH □□□□□

ORAJET®
ORAJET®