

ORAJET® 3551RA+

ProSlide™ Digital Printing

000000

000 PVC000000000000000000000000

00000

000 PVC00 , 0.07 00

000

00 PE00 RaidAir0000000000 , 158 g / m²

000

00000000 , 00 , 00 , 000 , 0.03 00

00000

ORAGUARD® XP279

00000

000

000	000000000000000000000000	
	7 0	000
000	2 0	0 20 °C 50% 0000000000000000
00000000	00 , 00 , 00 , 00 , 000 , 000 , 0000 0.5%0000000	000
0000	00000 0.2 00 00000 0 00	0000 0000 FINAT TM 14
00000	00000000 130 % 00000000 150 %	EN ISO 5270000
0000	00000000 19 N /0000 00000000 19 N /0000	DIN EN ISO 527 00
0000	0000	100 000 /35°C 00000000 DIN EN ISO 9227 00

ORAJET® 3551 RA+
ProSlide™ Digital Printing

11/11

□□□□	-40 °C
□□□□	60 °C

□□□□□□□□

□□□□□

111

14 N / 25□□

2400000000

| FINAT™ 10000

444

1111

□□□□ 10 °C

1111

[illegible]

55555

ISO 9001
ORAJET® ORAJET Europe GmbH

ORAJET®
ORAJET®