

ORAJET® 3591

Digital Printing Film

000000

000 PVC0000000000000000

00000

000 PVC00 , 0.07 00

000

00 PE000000000000 , 143 g / m²

000

0000000 , 000 , 000000 , 0.024 00

00000

ORAGUARD® XP279

00000

000

000	0000000000000000	
	7 0	00000000000000000000
000	2 0	0 20 °C 50% 0000000000000000
00000000	00 , 00 , 00 , 00 , 000 , 000 , 0000 0.5%0000000	000
0000	00000 0.2 00 00000 0 00	0000 0000 FINAT TM 14
00000	00000000 130 % 00000000 150 %	EN ISO 5270000
0000	00000000 19 N /0000 00000000 19 N /0000	DIN EN ISO 527 00
000	0000 -40 °C 0000 60 °C	0000000000



ORAJET® 3591

Digital Printing Film

55555

111

8 N / 25□□

24□□□□□□

| FINAT™ 10000

□□□□

1111

□□□□ 10 °C

10 °C

11

- [3591_3591RA_C-s1,d0 - Mineralischer Untergrund - Klassifizierung nach DIN EN 13501-1 - de.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)

□□□□

[illegible]

□□□□□





[illegible]

☐ ☐

ORAFOL

ORAJET® □ ORAFOL Europe GmbH □□□□□

ORAJET®
ORAJET®