

ORAJET® 3591RA
Digital Printing Film

000000

000 PVC0000000000

00000

000 PVC00 , 0.07 00

000

00 PE00 RaidAir0000000000 , 143 g / m²

000

00000000 , 000 , 00 , 0.03 00

00000

ORAGUARD® XP279

00000

000

000

0000000000000000

7 0

0000000000000000000000

000

2 0

0 20 °C 0 50% 0000000000000000

00000000

00 , 00 , 00 , 00 , 000 , 000 ,
0000 0.5%0000000

000

0000

00000 0.2 00
00000 0 00

0000 | 0000 FINAT TM 14

000000

00000000 130 %
00000000 150 %

DIN EN ISO 527

0000

00000000 19 N /0000
00000000 19 N /0000

DIN EN ISO 527

000

0000 -40 °C
0000 60 °C

0000000000

OAJET® 3591 RA

Digital Printing Film

□ □ □ □ □

333

8 N / 25□□

24000000

| 0000

FINAT TM 1

□□□□

□□□□

□□□□ 10 °C

10 °C

11

- [3591_3591RA_C-s1,d0 - Mineralischer Untergrund - Klassifizierung nach DIN EN 13501-1 - de.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3591_3591RA_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)

□ □ □ □

[illegible]

□ □ □ □ □





□ □

ORAFOL

ORAJET® □ ORAFOL Europe GmbH □□□□□

ORAJET®
ORAJET®