

ORAJET® 3620
Digital Printing Film

000000

0 PVC000000000000000000000000

00000

00 PVC00 , 0.08 00

0000

00000000 , 137 g / m²

0000

000000 , 000 , 00 , 0.019 00

00000

000

0000	000000000000000000000000		
	4 0		
0000	2 0		0 20 °C 50% 0000000000000000
00000	00000	0.4 00	0000 FINAT TM 14
	00000	0 00	
000000	00000000	130 %	DIN EN ISO 527
	00000000	150 %	
00000	00000000	19 N / 0000	DIN EN ISO 527
	00000000	19 N / 0000	
0000	0000	-40 °C	0000000000000000
	0000	60 °C	

000000

0000	7 N / 2500	2400000000000000000000	FINAT TM 1
------	------------	------------------------	------------

00000

00000	0000	10 °C
-------	------	-------



ORAJET® 3620

Digital Printing Film

22

- [3620_C-s1,d0 - Mineralischer Untergrund - Klassifizierung nach DIN EN 13501-1 - de.pdf](#) (Download)
- [3620_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3620_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3620_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3620_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)
- [3620_C-s1,d0 - mineral substrate - classification acc. to DIN EN 13501-1 - en.pdf](#) (Download)

□ □ □ □

[illegible]

□ □ □ □ □

ORAJET® 9001
ISO 9001
ORAJET® ORAFOL Europe GmbH

ORAJET®
ORAJET®