

# ORAJET® 3691

Digital Printing Film

000000

000000 PVC0000000000000000000000

00000

000000 PVC000 , 0.07 00

0000

00 PE000000000000 , 143 g / m<sup>2</sup>

0000

00000000 , 000000 , 0.024 00

00000

0000

0000

0000000000000000

5 0

0000

2 0

00

3 0

000000 ORAGUARD®236

0000

2 0

0 20 °C 0 50% 0000000000000000

000000000

00 , 00 , 00 , 00 , 000 , 000 ,  
0000 0.5%000000

0000

00000

000000 0.4 00  
000000 0 00

Verklebt auf Aluminium | FINAT TM 14, Durchschnittswert

000000

000000000 130 %  
000000000 150 %

DIN EN ISO 527

00000

00000000 19 N /0000  
00000000 19 N /0000

DIN EN ISO 527

00000

00000

100 000 /35°C | 00000000

DIN EN ISO 9227 00



# ORAJET® 3691

## Digital Printing Film

333

|      |        |
|------|--------|
| □□□□ | -40 °C |
| □□□□ | 60 °C  |

000000

□□□□□

33

8 N / 25□□

24h | FINAT™ 1

□ □ □ □

□□□□

□□□□ 10 °C

□ □ □ □

[illegible]

Page 10





[illegible][illegible]

ORAFOL

ORAJET® □ ORAFOL Europe GmbH □□□□□

ORAJET®  
ORAJET®