

ORACAL® 451

Banner Cal

000000

00000000 PVC000000000000

00000

000000 PVC00 , 0.08 00

000

00000000 , 137 g / m²

000

00000000 , 00 , 00 , 0.026 00

0000000

ORATAPE® HT95 Application Tape, ORATAPE® LT52 Application Tape, ORATAPE® LT95 Application Tape, ORATAPE® MT52 Application Tape, ORATAPE® MT72 Application Tape, ORATAPE® MT80P Application Tape, ORATAPE® MT95 Application Tape

00000

000

000	0000000000000000	
	3 0	
000	2 0	0 20 °C 50% 0000000000000000
00000000	00 , 00 , 00 , 00 , 000 , 000 , 000 0.5%000000	
0000	00000 0.4 00 00000 0 00	00000 FINAT TM 14 FINAT TM 14
00000	00000000 120 % 00000000 150 %	DIN EN ISO 527
0000	00000000 15 N /0000 00000000 15 N /0000	DIN EN ISO 527

ORACAL® 451

Banner Cal

□□□□	□□□□	100 □□□ /35°C □□□□□□	DIN EN ISO 9227 □□
□□□	□□□□ -40 °C	□□□□□□□□□□	
	□□□□ 60 °C		

□□□□□

14 N / 2500 2400000000 | 0000 FINAT TM 1

□ □ □ □

□□□□ □□□□ 10 °C

□ □ □ □

□ □

ORAFOL® Surface Cleaner

□ □ □ □ □

ORACAL® 日本製
ISO 9001 認証取得
品質保証
環境配慮
安全対策
ORAFOL Europe GmbH 代表取締役

ORACAL®
ORACAL®
ORAFOL
ORACAL® □