Description

This double-sided tape consists of a textile carrier that is layered on both sides with a modified dispersion acrylate adhesive. The adhesive is resistant to warmth, aging and plasticizers. The adhesive is lined with a white double-sided silicone paper.

Carrier

Rayon

Liner

55# paper, white, silicone-coated on both sides

Adhesive

Modified dispersion acrylate

Area of Use

This double-sided tape is suitable for the installment of carpet floors with PVC backing layers. Not appropriate for artificial stone floors or marble.

Technical Data

Thickness* (adhesive and carrier)	8.5-mil		
,			
Temperature resistance**	-4°F to +212°F		
Adhesive power*	3.43 lb/in	after 1 min	
(FINAT TM 1, on stainless steel, one side	3.65 lb/in	after 20 min	
covered with 2-mil polyester film)	4.11 lb/in	after 24 h	
Shear strength*	1 h	at 73°F	
(FINAT TM 8, on stainless steel, one side	5 min	at 158°F	
covered with 2-mil polyester film)			
Shelf life**	2 years		
Application temperature	> +59°F		
Available lengths	27-yard, 55-yard		
Available widths (in inches)	47		
	Slit rolls: 1 1/2, 2		

^{*} average ** in original packaging, at 68°F and 50% relative humidity

IMPORTANT NOTICE

All ORABOND™ products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND™ products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND™ products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.

All specifications are subject to change without prior notice.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

ORABOND™ is a registered trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA 1100 Oracal Parkway Black Creek, GA 31308 Phone: 888.672.2251 ORAFOL Americas – CT 120 Darling Drive Avon, CT 06001 Phone: 800.654.7570 ORAFOL Canada 2831 Bristol Circle Oakville, Ontario L6H 6X5 Phone: 888.727.3374

techsupport-americas@orafol.com - www.orafol.com