# **Description**

This double-sided tape consists of a paper tissue carrier, layered on both sides with a modified dispersion acrylate adhesive. It has very good initial and final adhesive strength and is highly resistant against aging and UV radiation. This tape is lined with a double-sided silicone paper.

## Carrier

Paper tissue

#### Liner

Brown paper, silicone-coated on both sides, 60#

#### **Adhesive**

Modified dispersion acrylate

## Area of Use

Suitable as an adhesive medium for polyester, PVC and polyethylene foams as well as for the splicing of paper, cardboard and film rolls. Ideal for the attachment of displays and advertisements.

#### Technical Data

recililical Data		
Thickness* (adhesive and carrier)	6-mil	
Temperature resistance	-40°F to +248°F	
LoopTack* (FINAT TM 9)	3.43 lb/in	
Adhesive power*	4.57 lb/in	after 1 min
(FINAT TM 1, on stainless steel, one side	5.48 lb/in	after 20 min
covered with 2-mil polyester film)	6.40 lb/in	after 24 h
Shear strength*	48 h	at 73°F
(FINAT TM 8, on stainless steel, one side	15 min	at 158°F
covered with 2-mil polyester film)		
Temperature resistance* (S.A.F.T.)	230°F	
Shelf life**	2 years	
Application temperature	> +59°F	
Available lengths	55-yards	
Available widths (in inches)	39	
	slit rolls: 1/2, 3/4, 1, 1 1/2, 2, 3, 4	

<sup>\*\*</sup> in original packaging, at 68°F and 50% relative humidity

## **IMPORTANT NOTICE**

All ORABOND™ products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND™ products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND™ products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

ORABOND™ is a registered trademark of ORAFOL Europe GmbH.



ORAFOL Americas - GA 1100 Oracal Parkway Black Creek, GA 31308 Phone: 888.672.2251

ORAFOL Americas - CT 120 Darling Drive Avon, CT 06001 Phone: 800.654.7570

**ORAFOL** Canada 2831 Bristol Circle Oakville, Ontario L6H 6X5 Phone: 888.727.3374 techsupport-americas@orafol.com - www.orafol.com