

Description

This mounting tape consists of a white, closed-cell polyethylene foam coated on both sides with a rubber adhesive. The rubber adhesive adheres well among other things on apolar substrates. The double sided mounting tape is lined with a white silicone paper.

Carrier

Closed-cell polyethylene foam, white, 39.5 mil

Liner

White paper, both sides coated with silicone, 60#

Adhesive

Rubber

Area of use

For fixing of boards, displays and for a variety of household applications. A universal, economical product. Good adhesion also on rough surfaces.

Technical Data

Thickness* (adhesive + foam)	43.5-mil	
Density*	0.03 oz/in ³	
Temperature resistance	-40°F to +158°F	
Loop Tack* (FINAT TM 9)	7.99 lb/in	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min:	4.11 lb/in
	after 20 min:	4.11 lb/in
	after 24 hr:	4.11 lb/in
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 73°F:	>500 h
	at 158°F:	1 hour
Temperature resistance (S.A.F.T.)	167°F	
Shelf life**	2 years	
Application temperature	+59°F	
Available lengths	55-yards	
Available widths (in inches)	49	
	slit rolls: ½, ¾, 1, 1 ½, 2, 3, 4	

* average ** in original packaging, at 68°F and 50% relative humidity

IMPORTANT NOTICE

All ORABOND™ products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND™ products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND™ products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. ORABOND™ is a registered trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570
techsupport-americas@orafol.com – www.orafol.com

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374