

**Description**

This tape consists of a polyester film carrier coated on one side with a silicone rubber adhesive. Its adhesive has a high shear strength and temperature resistance. It is resistant towards aging and plasticisers.

**Carrier**

Polyester film, 1 mil

**Liner**

Hard PVC film, white, creped

**Adhesive**

Silicone rubber

**Area of Use**

This rip-resistant tape adheres well to adhesive-repellent materials and is therefore suitable for use with silicone coated papers and silicone coated films.

**Technical Data**

<b>Thickness*</b> (adhesive + carrier)	2.25-mil	
<b>Temperature resistance</b>	Up to +356°F	
<b>LoopTack*</b> (FINAT TM 9)	2.28 lb/in	
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel)	2.06 lb/in	after 1 min
	2.28 lb/in	after 20 min
	2.74 lb/in	after 24 h
<b>Shear strength*</b> (S.A.F.T. Test from 73°F up to 446°F)	>72 h	at 73°F
	>1 h	at 158°F
<b>Temperature resistance*</b> (S.A.F.T.)	248°F	
<b>Shelf life**</b>	6 months	
<b>Application temperature</b>	>59°F	
<b>Available lengths</b>	55-yards	
<b>Available widths</b> (in inches)	slit rolls: 1/2, 3/4, 1, 1 1/2, 2, 3, 4	

\* average \*\* in original packaging, at 68°F and 50% relative humidity

**IMPORTANT NOTICE**

All ORAFIX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFIX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFIX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use.

All specifications are subject to change without prior notice.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

ORAFIX® is a registered trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA  
1100 Oracal Parkway  
Black Creek, GA 31308  
Phone: 888.672.2251

ORAFOL Americas – CT  
120 Darling Drive  
Avon, CT 06001  
Phone: 800.654.7570

ORAFOL Canada  
2831 Bristol Circle  
Oakville, Ontario L6H 6X5  
Phone: 888.727.3374

techsupport-americas@orafol.com – www.orafolamericas.com