

## Description

ORALITE® 5019 UV Digital Printing Ink is designed for use with the ORALITE® UV Traffic Sign Printer. The product works best when used in combination with the following ORALITE® reflective films:

- ORALITE® 5500 Engineer Grade
- ORALITE® 5700 Engineer Grade Premium
- ORALITE® 5800 High Intensity Grade
- ORALITE® 5900 High Intensity Prismatic Grade
- ORALITE® 5930 Prismatic Construction Grade
- ORALITE® 6900 ASTM Type VIII Prismatic Grade
- ORALITE® 7900 ASTM Type IX Prismatic Grade

The printed material shall be laminated with a suitable ORALITE® Transparent Film in order to achieve a smooth finish and optimum durability.

## Color

When using ORALITE® 5019 UV Digital Printing Ink and the recommended materials and settings, printed signs will meet the specifications for color and luminance of their class according to ASTM D4956 and AASHTO M268. The following colors are available:

- ORALITE® UV Digital Printing Ink 5019-020 yellow
- ORALITE® UV Digital Printing Ink 5019-030 red
- ORALITE® UV Digital Printing Ink 5019-050 blue
- ORALITE® UV Digital Printing Ink 5019-060 green
- ORALITE® UV Digital Printing Ink 5019-080 brown
- ORALITE® UV Digital Printing Ink 5019-070 black (opaque)

## Product Handling and Processing

Safety	Please refer to the Safety Data Sheets (SDS) for detailed safety information.
Storage	Closed containers should be stored under the following conditions: 59 - 79° F [15 - 26°C]; 40 - 60% rel. humidity. Minimum shelf life is 9 months.
Printing	To meet the minimum reflectance values and colors, the transparent UV digital printing ink colors must be printed on white (010) sheeting only. Black ink may be used with other base sheeting colors. It is also necessary to choose the correct printing profiles during the pre-production for each reflective film.  The ORALITE® 5019 UV Digital Printing Inks can only be used with the ORALITE® UV Traffic Sign Printer with suitable RIP software and color profiles supplied by ORAFOL.
Lamination	The recommended overlay films are listed below. Selection of these is dependent on the base reflective sheeting used and the final performance and durability level required. Recommended overlay films: <ul style="list-style-type: none"><li>• ORALITE® 5051 Transparent Film</li><li>• ORALITE® 5061 Transparent Film</li><li>• ORALITE® 5062 Transparent Film</li></ul>



**Note:**

All ORALITE® products are manufactured within an ISO 9001:2008 controlled manufacturing environment and batch traceability is possible on the basis of the roll number.

**IMPORTANT NOTICE**

When using ORALITE® sheeting, please comply with relevant national specifications. ORAFOL recommends obtaining the current requirements from your local authority and ensure product conformance with such requirements. Please contact ORAFOL for further information.

All ORALITE® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORALITE® products is based upon research which the Company believes to be reliable, although, such information does not constitute a warranty. Because of the variety of uses of ORALITE® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure respectively. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. The self-adhesive reflective material can only be used for dry application. The low tensile strength of the material can make the removability of the reflective film more difficult. Please review applicable application information published by ORAFOL.

No warranty is given for purposes other than those listed in the Technical Datasheet or which are not processed according to ORAFOL's processing and handling instructions. The durability of the signs will depend on a variety of factors, including but not limited to substrate selection and preparation, compliance with recommended application guidelines, geographic area, exposure conditions and maintenance of the product and finished sign. Sign failures caused by the substrate or improper surface preparations are not the responsibility of ORAFOL. Please refer to the full warranty document available at [www.orafolamericas.com](http://www.orafolamericas.com) for detailed information.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

ORALITE® is a trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA  
1100 Oracal Parkway  
Black Creek, GA 31308  
Phone: 888.672.2251

ORAFOL Americas – CT  
120 Darling Drive  
Avon, CT 06001  
Phone: 800.654.7570  
techsupport-americas@orafol.com - [www.orafolamericas.com](http://www.orafolamericas.com)

ORAFOL Canada  
2831 Bristol Circle  
Oakville, Ontario L6H 6X5  
Phone: 888.727.3374