

Description

3.5-mil, construction grade, reflective catadioptric glass bead film. Available in white and orange alternating stripes.

Release Liner

90# PE-coated silicone paper

Adhesive

Solvent polyacrylate, permanent.

Area of Use

ORALITE® 5431 Construction Grade is specially developed for the manufacture of short-term outdoor, reflective traffic control and guidance signs which are made of polyolefinic material, i.e. road works signs. The material is perfect for uneven surfaces and is resistant to corrosion, solvents and scratches.

Technical Data

Thickness* (without liner and adhesive)	3.5-mil
Temperature resistance	adhered to aluminum, -40°F to +179°F
Adhesive power* (FINAT-TM 1 after 24h, stainless steel)	3.43 lb/in film tear
Shelf life**	2 years
Application Temperature	> +50° F
Minimum Life Expectancy*** (based on accepted application procedures on vertical surfaces)	4 years (unprinted)
Available Lengths	150' (50-yard)
Available Widths (in inches)	10
Print Compatibility	Solvent printing

* average ** in original packaging, at 68°F and 50% relative humidity *** standard central European climate

Minimum reflection data (DIN 67520, Part 1)

Table 1 – Specific coefficient of retroreflection R' in cd/lx/m ²									
Observation angle	0.2°			0.33°			2°		
	5°	30°	40°	5°	30°	40°	5°	30°	40°
white (010)	70	30	10	50	24	9	5	2.5	1.5
yellow (020)	50	22	7	35	16	6	3	1.5	1
red (030)	14.5	6	2	10	4	1.8	1	0.5	0.5
orange (035)	25	10	2.2	20	8	2.2	1.2	0.5	-



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374

techsupport-americas@orafol.com - www.orafolamericas.com

Note:

All ORALITE® products are manufactured within an ISO 9001:2008 controlled manufacturing environment and batch traceability is possible on the basis of the roll number.

IMPORTANT NOTICE

When using ORALITE® sheeting, please comply with relevant national specifications. ORAFOL recommends obtaining the current requirements from your local authority and ensure product conformance with such requirements. Please contact ORAFOL for further information.

All ORALITE® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORALITE® products is based upon research which the Company believes to be reliable, although, such information does not constitute a warranty. Because of the variety of uses of ORALITE® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure respectively. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. The self-adhesive reflective material can only be used for dry application. The low tensile strength of the material can make the removability of the reflective film more difficult. Please review applicable application information published by ORAFOL.

No warranty is given for purposes other than those listed in the Technical Datasheet or which are not processed according to ORAFOL's processing and handling instructions. The durability of the signs will depend on a variety of factors, including but not limited to substrate selection and preparation, compliance with recommended application guidelines, geographic area, exposure conditions and maintenance of the product and finished sign. Sign failures caused by the substrate or improper surface preparations are not the responsibility of ORAFOL. Please refer to the full warranty document available at www.orafolamericas.com for detailed information.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

ORALITE® is a trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374

techsupport-americas@orafol.com - www.orafolamericas.com