

ORATAPE HT55

Decorative Film Application Tape

Description

4.0 to 4.5-mil, semi-transparent application tape with a specially formulated high-tack adhesive allowing the tape to stick to silicone-coated release liners. Graphics stay flat with no tunneling after transfer tape is applied for smoother graphics and faster applications.

Adhesive

Natural rubber, high adhesive power

Area of Use

The special composition of the adhesive enables problem-free premasking of die-cut or computer cut vinyl graphics; especially decorative films, such as ORACAL® 631 Exhibition Calendered Film, ORACAL® 8810 Frosted Glass Cast Film, ORACAL® 8510 Translucent Etched Glass Calendered Film, and ORACAL® 8710 Dusted Glass Calendered Film.

Technical Data

Thickness* (carrier and adhesive)	4.0 to 4.5 mil
Adhesive power (FINAT TM-1, after 20 min.)	Adhered to stainless steel: 0.48 lb/in
Tensile strength	Along: >17 lb/in Across: > 17 lb/in
Elongation at break	Along: 3%
Shelf life**	1 year
Minimum Application temperature	> +60°F
Available lengths	300' (100-yard)
Available widths (in inches)	6.5, 12, 14, 24, 30, 48, 54

*average **in original packaging, at 68°F and at 50% relative humidity

IMPORTANT NOTICE

All ORATAPE® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORATAPE® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORATAPE® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. ORATAPE® is a registered trademark of ORAFOL Europe GmbH.



ORAFOL Americas – GA
1100 Oracal Parkway
Black Creek, GA 31308
Phone: 888.672.2251

ORAFOL Americas – CT
120 Darling Drive
Avon, CT 06001
Phone: 800.654.7570

ORAFOL Canada
2831 Bristol Circle
Oakville, Ontario L6H 6X5
Phone: 888.727.3374

techsupport-americas@orafol.com – www.orafol.com