

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ORALITE® 5018 Thinner

Further trade names

Thinner of Screen Printing Ink Series ORALITE® 5018
Verdüner für die Siebdruckfarbe Serie ORALITE® 5018
ORALITE® 5018 Thinner
ORALITE® 5018 Verdüner

UFI: PN2N-68P6-W84X-T1KW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Diluent. Reserved for industrial and professional use.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	ORAFOL Europe GmbH	
	Germany	
Street:	Orafolstraße 1	
Place:	D-16515 Oranienburg	
Telephone:	+ 49 3301 864 0	Telefax: + 49 3301 864 100
e-mail:	msds@orafol.de	
Internet:	www.orafol.com	

1.4. Emergency telephone number:

National Poison Information Service: In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Flammable liquid: Flam. Liq. 3
Hazard Statements:
Flammable liquid and vapour.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

2-methoxy-1-methylethyl acetate, reaction mass of ethylbenzene and xylene

Signal word: Warning

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 2 of 15

P243	Take action to prevent static discharges.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P314	Get medical advice/attention if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Diluent. Contains: Dipropylene Glycol Methyl Ether Acetate (CAS 88917-22-0), 2-butoxyethyl acetate, butylglycol acetate, 2-methoxy-1-methylethyl acetate, reaction mass of ethylbenzene and xylene

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	GHS Classification	
112-07-2	2-butoxyethyl acetate, butylglycol acetate	15 - < 20 %
	203-933-3	607-038-00-2
	01-2119475112-47	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4; H332 H312 H302	
108-65-6	2-methoxy-1-methylethyl acetate	15 - < 20 %
	203-603-9	607-195-00-7
	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H226 H336	
	reaction mass of ethylbenzene and xylene	5 - < 10 %
	905-588-0	01-2119488216-32
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
112-07-2	203-933-3	2-butoxyethyl acetate, butylglycol acetate	15 - < 20 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 2,66 mg/l (dusts or mists); dermal: LD50 = ca. 1500 mg/kg; oral: LD50 = ca. 1880 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	15 - < 20 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 6190 - 10000 mg/kg	
	905-588-0	reaction mass of ethylbenzene and xylene	5 - < 10 %
		inhalation: LC50 = 6700 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 12126 mg/kg; oral: LD50 = 3523 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 3 of 15

After inhalation

Provide fresh air. Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Take off immediately all contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water. Full water jet

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. Release of: Carbon dioxide (CO₂), Carbon monoxide. The vapour is heavier than air and may travel along the ground; distant ignition possible.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Remove all sources of ignition. Wear personal protection equipment (refer to section 8). Provide adequate ventilation.

For emergency responders

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up**For containment**

Large amounts of spillages: Cover drains. Shafts and sewers must be protected from entry of the product. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Small amounts of spillages: Wipe up with absorbent material (eg. cloth, fleece).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 4 of 15

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Do not eat, drink or smoke when using this product. Avoid contact with skin.

Avoid contact with eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep/Store only in original container.

7.3. Specific end use(s)

Diluent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
112-07-2	2-Butoxyethyl acetate	20	133		TWA (8 h)	WEL
		50	332		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 5 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
112-07-2	2-butoxyethyl acetate, butylglycol acetate			
Worker DNEL, acute	inhalation	local	333 mg/m ³	
Worker DNEL, acute	dermal	systemic	120 mg/kg bw/day	
Worker DNEL, acute	inhalation	systemic	775 mg/m ³	
Consumer DNEL, acute	dermal	systemic	72 mg/kg bw/day	
Consumer DNEL, acute	inhalation	systemic	499 mg/m ³	
Consumer DNEL, acute	oral	systemic	36 mg/kg bw/day	
Consumer DNEL, acute	inhalation	local	200 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	102 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	80 mg/m ³	
Consumer DNEL, long-term	oral	systemic	8,6 mg/kg bw/day	
Worker DNEL, long-term	dermal	systemic	169 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	133 mg/m ³	
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL, long-term	inhalation	systemic	275 mg/m ³	
Worker DNEL, acute	inhalation	local	550 mg/m ³	
Worker DNEL, long-term	dermal	systemic	796 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	33 mg/m ³	
Consumer DNEL, long-term	inhalation	local	33 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	320 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	36 mg/kg bw/day	
	reaction mass of ethylbenzene and xylene			
Worker DNEL, long-term	inhalation	systemic	221 mg/m ³	
Worker DNEL, acute	inhalation	systemic	442 mg/m ³	
Worker DNEL, long-term	inhalation	local	221 mg/m ³	
Worker DNEL, acute	inhalation	local	442 mg/m ³	
Worker DNEL, long-term	dermal	systemic	212 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	65,3 mg/m ³	
Consumer DNEL, acute	inhalation	systemic	260 mg/m ³	
Consumer DNEL, long-term	inhalation	local	65,3 mg/m ³	
Consumer DNEL, acute	inhalation	local	260 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	12,5 mg/kg bw/day	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 6 of 15

PNEC values

CAS No	Substance	
Environmental compartment		Value
112-07-2	2-butoxyethyl acetate, butylglycol acetate	
Freshwater		0,304 mg/l
Freshwater (intermittent releases)		0,56 mg/l
Marine water		0,03 mg/l
Freshwater sediment		2,03 mg/kg
Marine sediment		0,203 mg/kg
Secondary poisoning		60 mg/kg
Micro-organisms in sewage treatment plants (STP)		90 mg/l
Soil		0,415 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
Freshwater		0,635 mg/l
Freshwater (intermittent releases)		6,35 mg/l
Marine water		0,064 mg/l
Freshwater sediment		3,29 mg/kg
Marine sediment		0,329 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,29 mg/kg
	reaction mass of ethylbenzene and xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 7 of 15

supplier of these gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

Recommended material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material $\geq 0,5$ mm

Breakthrough time: ≥ 8 h

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection Filter type: A

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
pH-Value:	not determined

Changes in the physical state

Melting point:	not determined
Boiling point or initial boiling point and boiling range:	ca. 139,1 °C
Flash point:	27 °C
Sustaining combustion:	Not sustaining combustion

Flammability

Solid/liquid:	not applicable
Gas:	not applicable

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits:	1,21 vol. %
Upper explosion limits:	7 vol. %
Auto-ignition temperature:	333 °C

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	not determined
----------------------------	----------------

Oxidizing properties

The product is not: oxidising.

Vapour pressure: (at 20 °C)	5,02 hPa
--------------------------------	----------

Density:	0,96 g/cm ³
----------	------------------------

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
-------------------	--

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:	not determined
--	----------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 8 of 15

Relative vapour density: not determined

Evaporation rate: not determined

Solvent content: 100,00 %

9.2. Other information

Solid content: 0 %

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Materials to avoid: Strong acid, Oxidising agent, strong

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂).**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 9 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
112-07-2	2-butoxyethyl acetate, butylglycol acetate				
	oral	LD50 ca. 1880 mg/kg	Rat	Study report (1963)	OECD Guideline 401
	dermal	LD50 ca. 1500 mg/kg	Rabbit	Toxicol Appl Pharmac 51, 117-27 (1979)	Modification of the Draize 1959 method u
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) aerosol	LC50 2,66 mg/l	Rat		
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 6190 - 10000 mg/kg	Rat	Study report (1985)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1985)	OECD Guideline 402
	reaction mass of ethylbenzene and xylene				
	oral	LD50 3523 mg/kg	Rat	Study report (1986)	EU Method B.1
	dermal	LD50 12126 mg/kg	Rabbit	Publication (1962)	Single dermal dose under occlusion follo
	inhalation (4 h) vapour	LC50 6700 mg/l	Rat	Toxicol Appl Pharmacol 33:543-558. (1975)	EU Method B.2
	inhalation aerosol	ATE 1,5 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 10 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
112-07-2	2-butoxyethyl acetate, butylglycol acetate					
	Acute fish toxicity	LC50 > 20 - < 40 mg/l	96 h	Oncorhynchus mykiss	Toxicol Mech & meth 12, 255-63 (2002)	OECD Guideline 203
	Acute algae toxicity	ErC50 1570 mg/l	72 h	Pseudokirchneriella subcapitata	Toxicol Mech & meth 12, 255-63 (2002)	ISO 8692
	Acute crustacea toxicity	EC50 67,5 mg/l	48 h	Daphnia magna	Toxicol Mech & meth 12, 255-63 (2002)	ISO 6341
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 100 - 180 mg/l	96 h	Oncorhynchus mykiss	Study report (1987)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1986)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna	Study report (1987)	EU Method C.2
	Fish toxicity	NOEC 47,5 mg/l	14 d	Oryzias latipes	Study report (1998)	OECD Guideline 204
	Crustacea toxicity	NOEC >= 100 mg/l	21 d	Daphnia magna	Study report (1998)	OECD Guideline 211
	reaction mass of ethylbenzene and xylene					
	Acute fish toxicity	LC50 8,4 mg/l	96 h	Oncorhynchus mykiss	Ecotoxicology and Environmental Safety.	OECD Guideline 203
	Acute algae toxicity	ErC50 4,9 mg/l	72 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety.	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 3,4 mg/l	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Fish toxicity	NOEC > 1,3 mg/l	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve	Fish were exposed in artificial streams
	Crustacea toxicity	NOEC 1,17 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Acute bacteria toxicity	(> 175 mg/l)	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (OECD Guideline 209

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 11 of 15

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
112-07-2	2-butoxyethyl acetate, butylglycol acetate			
	OECD 301F	88%	28	
	Readily biodegradable (according to OECD criteria).			
108-65-6	2-methoxy-1-methylethyl acetate			
	OECD 301F	83%	28	
	Readily biodegradable (according to OECD criteria).			
	OECD 302B	100%	28	
	Readily biodegradable (according to OECD criteria).			
	reaction mass of ethylbenzene and xylene			
	OECD 301F	90%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-07-2	2-butoxyethyl acetate, butylglycol acetate	1,51
108-65-6	2-methoxy-1-methylethyl acetate	1,2
	reaction mass of ethylbenzene and xylene	3,2

BCF

CAS No	Chemical name	BCF	Species	Source
	reaction mass of ethylbenzene and xylene	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

The product has not been tested.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. The waste code has to be identified in agreement with the disposal company or the competent authority.

List of Wastes Code - residues/unused products

080312 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of printing inks; waste ink containing hazardous substances; hazardous waste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 12 of 15

List of Wastes Code - used product

080312 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of printing inks; waste ink containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080312 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of printing inks; waste ink containing hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT RELATED MATERIAL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint related material
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT RELATED MATERIAL
14.3. Transport hazard class(es): 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 13 of 15

14.4. Packing group:

III

Hazard label:

3



Special Provisions:

163, 223, 367, 955

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

UN 1263

14.2. UN proper shipping name:

PAINT RELATED MATERIAL

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Special Provisions:

A3 A72 A192

Limited quantity Passenger:

10 L

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

Warning: flammable liquids. Keep away from heat.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 48

2010/75/EU (VOC):

100 % (960 g/l)

2004/42/EC (VOC):

100 % (960 g/l)

Information according to 2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Additional information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 14 of 15

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: none

This mixture contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s):

1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Thinner

Revision date: 19.05.2021

Product code: 345900034

Page 15 of 15

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)