

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ORALITE® 5018 Screen Printing Ink (000)

Further trade names

ORALITE® Siebdruckfarbe 5018-000
Colour: transparent (000)

UFI: QUE0-AMG6-YN42-3EFR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Colour (Screen Printing Ink)

Uses advised against

Do not use for private purposes (household). Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	ORAFOL Europe GmbH	
	Germany	
Street:	Orafolstraße 1	
Place:	D-16515 Oranienburg	
Telephone:	+ 49 3301 864 0	Telefax: + 49 3301 864 100
e-mail:	msds@orafol.de	
Internet:	www.orafol.com	

1.4. Emergency telephone number:

National Poison Information Service: In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Flammable liquid: Flam. Liq. 3
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
Flammable liquid and vapour.
Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 2 of 15

P243	Take action to prevent static discharges.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH208	Contains Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.
--------	---

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
1330-20-7	xylene	5 - < 10 %
	215-535-7	
	601-022-00-9	
	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412	
108-65-6	2-methoxy-1-methylethyl acetate	5 - < 10 %
	203-603-9	
	607-195-00-7	
	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H226 H336	
112-07-2	2-butoxyethyl acetate, butylglycol acetate	5 - < 10 %
	203-933-3	
	607-038-00-2	
	01-2119475112-47	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4; H332 H312 H302	
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	< 1 %
	915-687-0	
	01-2119491304-40	
	Skin Sens. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H317 H400 H410	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If eye irritation persists: Get medical

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 3 of 15

advice/attention.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. Hazardous combustion products: Carbon dioxide (CO₂), Carbon monoxide (CO), Sulphur oxides, Silicon dioxide (SiO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. The danger areas must be delimited and identified using relevant warning and safety signs. Heating causes rise in pressure with risk of bursting. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Beware of reignition.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Use personal protection equipment. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 4 of 15

Further information on handling

Thermal hazards: Hazardous decomposition products: Methyl methacrylate, dodecyl methacrylate, Phenol, Sulphur dioxide (SO₂).

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Unsuitable container/equipment material: Copper, Aluminium, Zinc.

7.3. Specific end use(s)

Colour (Screen Printing Ink)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
112-07-2	2-Butoxyethyl acetate	20	133		TWA (8 h)	WEL
		50	332		STEL (15 min)	WEL
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 5 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1330-20-7	xylene			
Worker DNEL, long-term		inhalation	systemic	221 mg/m ³
Worker DNEL, acute		inhalation	systemic	442 mg/m ³
Worker DNEL, long-term		inhalation	local	221 mg/m ³
Worker DNEL, acute		inhalation	local	442 mg/m ³
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m ³
Consumer DNEL, acute		inhalation	systemic	260 mg/m ³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m ³
Consumer DNEL, acute		inhalation	local	260 mg/m ³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	12,5 mg/kg bw/day
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL, long-term		inhalation	systemic	275 mg/m ³
Worker DNEL, acute		inhalation	local	550 mg/m ³
Worker DNEL, long-term		dermal	systemic	796 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	33 mg/m ³
Consumer DNEL, long-term		inhalation	local	33 mg/m ³
Consumer DNEL, long-term		dermal	systemic	320 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	36 mg/kg bw/day
112-07-2	2-butoxyethyl acetate, butylglycol acetate			
Worker DNEL, acute		inhalation	local	333 mg/m ³
Worker DNEL, acute		dermal	systemic	120 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	775 mg/m ³
Consumer DNEL, acute		dermal	systemic	72 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	499 mg/m ³
Consumer DNEL, acute		oral	systemic	36 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	200 mg/m ³
Consumer DNEL, long-term		dermal	systemic	102 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	80 mg/m ³
Consumer DNEL, long-term		oral	systemic	8,6 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	169 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	133 mg/m ³
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			
Worker DNEL, acute		dermal	systemic	2,5 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	2,35 mg/m ³
Worker DNEL, long-term		inhalation	systemic	0,68 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 6 of 15

Consumer DNEL, acute	dermal	systemic	1,25 mg/kg bw/day
Consumer DNEL, acute	inhalation	systemic	0,58 mg/m ³
Consumer DNEL, acute	oral	systemic	1,25 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,17 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,05 mg/kg bw/day

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 7 of 15

PNEC values

CAS No	Substance	Value
Environmental compartment		
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
Freshwater		0,635 mg/l
Freshwater (intermittent releases)		6,35 mg/l
Marine water		0,064 mg/l
Freshwater sediment		3,29 mg/kg
Marine sediment		0,329 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,29 mg/kg
112-07-2	2-butoxyethyl acetate, butylglycol acetate	
Freshwater		0,304 mg/l
Freshwater (intermittent releases)		0,56 mg/l
Marine water		0,03 mg/l
Freshwater sediment		2,03 mg/kg
Marine sediment		0,203 mg/kg
Secondary poisoning		60 mg/kg
Micro-organisms in sewage treatment plants (STP)		90 mg/l
Soil		0,415 mg/kg
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Freshwater		0,002 mg/l
Freshwater (intermittent releases)		0,009 mg/l
Marine water		0 mg/l
Freshwater sediment		1,05 mg/kg
Marine sediment		0,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		1 mg/l
Soil		0,21 mg/kg

Additional advice on limit values

TRGS 900, 2-butoxyethyl acetate; butylglycol acetate & 2-methoxypropyl acetate & 2-methoxypropyl acetate:: Aerosol, vapour May be absorbed through the skin.

2-methoxypropyl acetate: Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

8.2. Exposure controls

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 8 of 15



Appropriate engineering controls

Use explosion-proof ventilating equipment.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye protection/face protection.

Hand protection

Suitable gloves type: Butyl caoutchouc (butyl rubber). Use gloves only once.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	transparent	
pH-Value:		not determined
Changes in the physical state		
Melting point:		not determined
Initial boiling point and boiling range:		ca. 139,1 °C
Flash point:		27 °C
Flammability		
Solid:		not applicable
Gas:		not applicable
Explosive properties		
Vapours can form explosive mixtures with air.		
Lower explosion limits:		1,21 vol. %
Upper explosion limits:		7 vol. %
Ignition temperature:		>210 °C
Auto-ignition temperature		
Solid:		not applicable
Gas:		not applicable
Decomposition temperature:		not determined

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 9 of 15

Oxidizing properties

Not oxidising.

Vapour pressure: 5,02 hPa
(at 20 °C)Density: 1,01 g/cm³Water solubility: The study does not need to be conducted
because the substance is known to be
insoluble in water.**Solubility in other solvents**

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

Solvent content: 62 - 67%

9.2. Other information

Solid content: 33 - 38%

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable. In use, may form flammable/explosive vapour-air mixture.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Unsuitable container/equipment material: Copper, Aluminium, Zinc.

Avoid: Strong acid, Oxidising agent.

10.6. Hazardous decomposition productsThermal hazards: Hazardous decomposition products: Methyl methacrylate, dodecyl methacrylate, Phenol, Sulphur dioxide (SO₂).Hazardous combustion products: Carbon dioxide (CO₂), Carbon monoxide (CO), Sulphur oxides, Silicon dioxide (SiO₂).**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 10 of 15

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 > 4000 mg/kg	Rat	Study report (1986)	EU Method B.1
	dermal	LD50 12126 mg/kg	Rabbit	Publication (1962)	Single dermal dose under occlusion follo
	inhalation (4 h) vapour	LC50 6247 mg/l	Rat	Study report (1986)	EPA OPP 81-3
	inhalation aerosol	ATE 1,5 mg/l			
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 6190 mg/kg	Rat	Study report (1985)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1985)	OECD Guideline 402
112-07-2	2-butoxyethyl acetate, butylglycol acetate				
	oral	LD50 ca. 1880 mg/kg	Rat	Study report (1963)	OECD Guideline 401
	dermal	LD50 ca. 1500 mg/kg	Rabbit	Toxicol Appl Pharmac 51, 117-27 (1979)	Modification of the Draize 1959 method u
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) aerosol	LC50 2,66 mg/l	Rat		
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate				
	oral	LD50 3230 mg/kg	Rat	Study report (1981)	OECD Guideline 423
	dermal	LD50 > 3170 mg/kg	Rat	Study report (1975)	OECD Guideline 402

SECTION 12: Ecological information
12.1. Toxicity

Harmful to aquatic life with long lasting effects.

The product has not been tested. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1330-20-7	xylene					
	Acute fish toxicity	LC50 8,4 mg/l	96 h	Oncorhynchus mykiss	Ecotoxicology and Environmental Safety.	OECD Guideline 203
	Acute algae toxicity	ErC50 4,9 mg/l	72 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety.	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l > 3,4	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Fish toxicity	NOEC mg/l > 1,3	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve	Fish were exposed in artificial streams
	Crustacea toxicity	NOEC mg/l 1,17	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Acute bacteria toxicity	(> 175 mg/l)	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (OECD Guideline 209
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 mg/l > 100	96 h	Oryzias latipes	Study report (1998)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l > 1000	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 408 mg/l	48 h	Daphnia magna	Study report (1980)	OECD Guideline 202
	Fish toxicity	NOEC mg/l 47,5	14 d	Oryzias latipes	Study report (1998)	OECD Guideline 204
	Crustacea toxicity	NOEC mg/l >= 100	21 d	Daphnia magna	Study report (1998)	OECD Guideline 211
112-07-2	2-butoxyethyl acetate, butylglycol acetate					
	Acute fish toxicity	LC50 40 mg/l > 20 - <	96 h	Oncorhynchus mykiss	Toxicol Mech & meth 12, 255-63 (2002)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l 1570	72 h	Pseudokirchneriella subcapitata	Toxicol Mech & meth 12, 255-63 (2002)	ISO 8692
	Acute crustacea toxicity	EC50 mg/l 67,5	48 h	Daphnia magna	Toxicol Mech & meth 12, 255-63 (2002)	ISO 6341
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate					
	Acute fish toxicity	LC50 0,9 mg/l	96 h	Danio rerio	Study report (2010)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l 1,68	72 h	Desmodesmus subspicatus	Study report (2010)	OECD Guideline 201
	Acute crustacea toxicity	EC50 20 mg/l	48 h	Daphnia magna		
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211
	Acute bacteria toxicity	(> 100 mg/l)	3 h			

12.2. Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 12 of 15

The product has not been tested.

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
112-07-2	2-butoxyethyl acetate, butylglycol acetate	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	88 %	28	
	Readily biodegradable (according to OECD criteria).				
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	OECD 301F; ISO 9408; 92/69/EWG, C.4-D	38%	28	
	Not readily biodegradable (according to OECD criteria) Moderately/partially biodegradable. 38 % DOC reduction.				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1330-20-7	xylene	3,2
108-65-6	2-methoxy-1-methylethyl acetate	1,2
112-07-2	2-butoxyethyl acetate, butylglycol acetate	1,51
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	2,37

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	< 9,7	Cyprinus carpio	Study report (1981)

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Dispose of this material and its container to hazardous or special waste collection point. Consult the appropriate local waste disposal expert about waste disposal.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 13 of 15

substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 163 367 650
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 30
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 163 367 650
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: 163, 223, 367, 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1263

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 14 of 15

14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3 A72 A192
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: flammable liquids

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: xylene; 2-methoxy-1-methylethyl acetate

Entry 57: cyclohexane

2010/75/EU (VOC): 66,09 % (667,509 g/l)

2004/42/EC (VOC): 66,09 % (667,509 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ORALITE® 5018 Screen Printing Ink (000)

Revision date: 11.01.2021

Product code: SDF5018-000N

Page 15 of 15

DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)