

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 1 of 18

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

ORALITE® 5018 Screen Printing Ink (080)

#### Further trade names

ORALITE® Siebdruckfarbe 5018-080

Colour: brown (080)

UFI: QHN2-7MNS-YN4Y-9HNC

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Colour (Screen Printing Ink)

#### Uses advised against

Do not use for private purposes (household). Reserved for industrial and professional use.

### 1.3. Details of the supplier of the safety data sheet

Company name:	ORAFOL Europe GmbH	
	Germany	
Street:	Orafolstraße 1	
Place:	D-16515 Oranienburg	
Telephone:	+ 49 3301 864 0	Telefax: + 49 3301 864 100
e-mail:	msds@orafol.de	
Internet:	www.orafol.com	

### 1.4. Emergency telephone number:

National Poison Information Service: In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

Signal word: Warning

Pictograms:



#### Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 2 of 18

- H319 Causes serious eye irritation.  
H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take action to prevent static discharges.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

**Special labelling of certain mixtures**

- EUH208 Contains Naphthenic acids, nickel salts, Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

according to Regulation (EC) No 1907/2006

**ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 3 of 18

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1330-20-7	xylene			5 - < 10 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
112-07-2	2-butoxyethyl acetate, butylglycol acetate			5 - < 10 %
	203-933-3	607-038-00-2	01-2119475112-47	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4; H332 H312 H302			
108-65-6	2-methoxy-1-methylethyl acetate			5 - < 10 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H226 H336			
25086-48-0	Vinyl Chloride vinyl acetate vinyl alcohol resin			1 - < 5 %
	607-539-6			
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335			
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			< 1 %
	915-687-0		01-2119491304-40	
	Skin Sens. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H317 H400 H410			
61788-71-4	Naphthenic acids, nickel salts			< 1 %
	263-000-1		01-2120796206-47	
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

**After inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

**After contact with skin**

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. If eye irritation persists: Get medical advice/attention.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 4 of 18

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### **Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

###### **Unsuitable extinguishing media**

Full water jet

##### 5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. Hazardous combustion products: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide (CO), Sulphur oxides, Silicon dioxide (SiO<sub>2</sub>).

##### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. The danger areas must be delimited and identified using relevant warning and safety signs. Heating causes rise in pressure with risk of bursting. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Beware of reignition.

##### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Provide adequate ventilation.

##### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

##### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

##### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

###### **Advice on safe handling**

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

###### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

###### **Further information on handling**

Thermal hazards: Hazardous decomposition products: Methyl methacrylate, dodecyl methacrylate, Phenol, Sulphur dioxide (SO<sub>2</sub>).

##### 7.2. Conditions for safe storage, including any incompatibilities

###### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks,

according to Regulation (EC) No 1907/2006

## ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 5 of 18

open flames and other ignition sources. No smoking. Keep/Store only in original container.

### Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

### Further information on storage conditions

Unsuitable container/equipment material: Copper, Aluminium, Zinc.

### 7.3. Specific end use(s)

Colour (Screen Printing Ink)

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
112-07-2	2-Butoxyethyl acetate	20	133		TWA (8 h)	WEL
		50	332		STEL (15 min)	WEL
7727-43-7	Barium sulphate, inhalable dust	-	10		TWA (8 h)	WEL
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

#### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

according to Regulation (EC) No 1907/2006

## ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 6 of 18

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
1330-20-7	xylene			
Worker DNEL, long-term		inhalation	systemic	221 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	442 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	221 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	442 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	12,5 mg/kg bw/day
112-07-2	2-butoxyethyl acetate, butylglycol acetate			
Worker DNEL, acute		inhalation	local	333 mg/m <sup>3</sup>
Worker DNEL, acute		dermal	systemic	120 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	775 mg/m <sup>3</sup>
Consumer DNEL, acute		dermal	systemic	72 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	499 mg/m <sup>3</sup>
Consumer DNEL, acute		oral	systemic	36 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	200 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	102 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	80 mg/m <sup>3</sup>
Consumer DNEL, long-term		oral	systemic	8,6 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	169 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	133 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL, long-term		inhalation	systemic	275 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	550 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	796 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	33 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	33 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	320 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	36 mg/kg bw/day
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			
Worker DNEL, acute		dermal	systemic	2,5 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	2,35 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	0,68 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 7 of 18

Consumer DNEL, acute	dermal	systemic	1,25 mg/kg bw/day
Consumer DNEL, acute	inhalation	systemic	0,58 mg/m <sup>3</sup>
Consumer DNEL, acute	oral	systemic	1,25 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,17 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	0,05 mg/kg bw/day
<b>61788-71-4</b>	<b>Naphthenic acids, nickel salts</b>		
Worker DNEL, long-term	inhalation	systemic	0,46 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	963 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	0,46 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	14,8 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	81,5 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	0,93 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	0,19 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,11 mg/kg bw/day
<b>7727-43-7</b>	<b>Barium Sulfate</b>		
Worker DNEL, long-term	inhalation	systemic	10 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	10 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	systemic	10 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	13000 mg/kg bw/day

according to Regulation (EC) No 1907/2006

## ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 8 of 18

### PNEC values

CAS No	Substance	Value
Environmental compartment		
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
112-07-2	2-butoxyethyl acetate, butylglycol acetate	
Freshwater		0,304 mg/l
Freshwater (intermittent releases)		0,56 mg/l
Marine water		0,03 mg/l
Freshwater sediment		2,03 mg/kg
Marine sediment		0,203 mg/kg
Secondary poisoning		60 mg/kg
Micro-organisms in sewage treatment plants (STP)		90 mg/l
Soil		0,415 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
Freshwater		0,635 mg/l
Freshwater (intermittent releases)		6,35 mg/l
Marine water		0,064 mg/l
Freshwater sediment		3,29 mg/kg
Marine sediment		0,329 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,29 mg/kg
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Freshwater		0,002 mg/l
Freshwater (intermittent releases)		0,009 mg/l
Marine water		0 mg/l
Freshwater sediment		1,05 mg/kg
Marine sediment		0,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		1 mg/l
Soil		0,21 mg/kg
61788-71-4	Naphtenic acids, nickel salts	
Freshwater		0,00615 mg/l
Freshwater (intermittent releases)		0 mg/l
Marine water		0,000615 mg/l
Freshwater sediment		30,73 mg/kg
Marine sediment		3,07 mg/kg
Secondary poisoning		1,11 mg/kg



according to Regulation (EC) No 1907/2006

## ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 9 of 18

Micro-organisms in sewage treatment plants (STP)	0,142 mg/l
Soil	6,138 mg/kg
7727-43-7	Barium Sulfate
Freshwater	0,115 mg/l
Freshwater sediment	600,4 mg/kg
Micro-organisms in sewage treatment plants (STP)	62,2 mg/l
Soil	207,7 mg/kg

### Additional advice on limit values

TRGS 900, 2-butoxyethyl acetate; butylglycol acetate & 2-methoxypropyl acetate & 2-methoxypropyl acetate::  
Aerosol, vapour May be absorbed through the skin.

2-methoxypropyl acetate: Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

### 8.2. Exposure controls



#### Appropriate engineering controls

Use explosion-proof ventilating equipment.

#### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Suitable eye protection: goggles.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Suitable gloves type: Butyl caoutchouc (butyl rubber). Use gloves only once.

#### Skin protection

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Collect spillage.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	brown
pH-Value:	not determined

#### Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	ca. 139,1 °C

according to Regulation (EC) No 1907/2006

**ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 10 of 18

Flash point: 27 °C

**Flammability**

Solid: not applicable

Gas: not applicable

**Explosive properties**

The product is not: Explosive. Vapours can form explosive mixtures with air.

Lower explosion limits: 1,21 vol. %

Upper explosion limits: 7 vol. %

Ignition temperature: &gt;210 °C

**Auto-ignition temperature**

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties**

Not oxidising.

Vapour pressure: 5,02 hPa

(at 20 °C)

Density: 1,02 g/cm<sup>3</sup>

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

**Solubility in other solvents**

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

Solvent content: 62 - 67%

**9.2. Other information**

Solid content: 33 - 38%

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Flammable. In use, may form flammable/explosive vapour-air mixture.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

Unsuitable container/equipment material: Copper, Aluminium, Zinc.

Avoid: Strong acid, Oxidising agent.

**10.6. Hazardous decomposition products**

Thermal hazards: Hazardous decomposition products: Methyl methacrylate, dodecyl methacrylate, Phenol,

according to Regulation (EC) No 1907/2006

**ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 11 of 18

 Sulphur dioxide (SO<sub>2</sub>).

 Hazardous combustion products: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide (CO), Sulphur oxides, Silicon dioxide (SiO<sub>2</sub>).

**SECTION 11: Toxicological information**
**11.1. Information on toxicological effects**
**Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	oral	LD50 > 4000 mg/kg	Rat	Study report (1986)	EU Method B.1
	dermal	LD50 12126 mg/kg	Rabbit	Publication (1962)	Single dermal dose under occlusion follo
	inhalation (4 h) vapour	LC50 6247 mg/l	Rat	Study report (1986)	EPA OPP 81-3
	inhalation aerosol	ATE 1,5 mg/l			
112-07-2	2-butoxyethyl acetate, butylglycol acetate				
	oral	LD50 ca. 1880 mg/kg	Rat	Study report (1963)	OECD Guideline 401
	dermal	LD50 ca. 1500 mg/kg	Rabbit	Toxicol Appl Pharmac 51, 117-27 (1979)	Modification of the Draize 1959 method u
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) aerosol	LC50 2,66 mg/l	Rat		
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 6190 mg/kg	Rat	Study report (1985)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1985)	OECD Guideline 402
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate				
	oral	LD50 3230 mg/kg	Rat	Study report (1981)	OECD Guideline 423
	dermal	LD50 > 3170 mg/kg	Rat	Study report (1975)	OECD Guideline 402
61788-71-4	Naphthenic acids, nickel salts				
	oral	LD50 361,9 mg/kg	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425
	dermal	LD50 > 20000 mg/kg	Rabbit	Study report (1979)	other: CFR 16 1500.40

**Additional information on tests**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information**
**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

The product has not been tested. The ecotoxicological properties of this mixture are determined by the



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### **ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 12 of 18

ecotoxicological properties of the single components (see section 3).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 13 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1330-20-7	xylene					
	Acute fish toxicity	LC50 8,4 mg/l	96 h	Oncorhynchus mykiss	Ecotoxicology and Environmental Safety.	OECD Guideline 203
	Acute algae toxicity	ErC50 4,9 mg/l	72 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety.	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l > 3,4	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Fish toxicity	NOEC mg/l > 1,3	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve	Fish were exposed in artificial streams
	Crustacea toxicity	NOEC mg/l 1,17	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	other: US EPA 600/4-91-003
	Acute bacteria toxicity	(> 175 mg/l)	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (	OECD Guideline 209
112-07-2	2-butoxyethyl acetate, butylglycol acetate					
	Acute fish toxicity	LC50 > 20 - < 40 mg/l	96 h	Oncorhynchus mykiss	Toxicol Mech & meth 12, 255-63 (2002)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l 1570	72 h	Pseudokirchneriella subcapitata	Toxicol Mech & meth 12, 255-63 (2002)	ISO 8692
	Acute crustacea toxicity	EC50 mg/l 67,5	48 h	Daphnia magna	Toxicol Mech & meth 12, 255-63 (2002)	ISO 6341
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 mg/l > 100	96 h	Oryzias latipes	Study report (1998)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l > 1000	72 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l 408	48 h	Daphnia magna	Study report (1980)	OECD Guideline 202
	Fish toxicity	NOEC mg/l 47,5	14 d	Oryzias latipes	Study report (1998)	OECD Guideline 204
	Crustacea toxicity	NOEC mg/l >= 100	21 d	Daphnia magna	Study report (1998)	OECD Guideline 211
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate					
	Acute fish toxicity	LC50 mg/l 0,9	96 h	Danio rerio	Study report (2010)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l 1,68	72 h	Desmodesmus subspicatus	Study report (2010)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l 20	48 h	Daphnia magna		
	Crustacea toxicity	NOEC mg/l 1	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211
	Acute bacteria toxicity	(> 100 mg/l)	3 h			
61788-71-4	Naphthenic acids, nickel salts					

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 14 of 18

	Acute fish toxicity	LC50	10 mg/l	96 h	Oncorhynchus mykiss	Environmental Toxicology and Chemistry.	other: ASTM E729-80
	Acute algae toxicity	ErC50 mg/l	ca. 23,8	72 h	Pseudokirchneriella subcapitata	Robust study summary (2010)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729
	Algae toxicity	NOEC mg/l	< 0,1	14 d	Navicula pelliculosa	Environ. Pollut. 20(3):131-137. (1979)	other: not reported
	Crustacea toxicity	NOEC mg/l	> 0,494	28 d	Tubifex tubifex	Environmental Toxicology and Chemistry,	other: ASTM E1706-05
	Acute bacteria toxicity	(33 mg/l)		0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192

**12.2. Persistence and degradability**

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
112-07-2	2-butoxyethyl acetate, butylglycol acetate			
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	88 %	28	
	Readily biodegradable (according to OECD criteria).			
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			
	OECD 301F; ISO 9408; 92/69/EWG, C.4-D	38%	28	
	Not readily biodegradable (according to OECD criteria) Moderately/partially biodegradable. 38 % DOC reduction.			

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
1330-20-7	xylene	3,2
112-07-2	2-butoxyethyl acetate, butylglycol acetate	1,51
108-65-6	2-methoxy-1-methylethyl acetate	1,2
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	2,37
61788-71-4	Naphthenic acids, nickel salts	> 2,05 - < 13,25

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ORALITE® 5018 Screen Printing Ink (080)**

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 15 of 18

**BCF**

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E
1065336-91-5	Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	< 9,7	Cyprinus carpio	Study report (1981)
61788-71-4	Naphthenic acids, nickel salts	39	Chlorella salina	J. Mar. Biol. Ass. U

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The product has not been tested.

**12.6. Other adverse effects**

No information available.

**Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Contains: Copper.

The product contains organically bound halogen as per formulation. It may increase the AOX value when discharged from treatment plants or into natural waters. AOX: Chlorine

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**


Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Dispose of this material and its container to hazardous or special waste collection point. Consult the appropriate local waste disposal expert about waste disposal.

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information**
**Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	PAINT
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
	
Classification code:	F1
Special Provisions:	163 367 650
Limited quantity:	5 L
Excepted quantity:	E1

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 16 of 18

Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

#### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	Paint
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Special Provisions:	163 367 650
Limited quantity:	5 L
Excepted quantity:	E1

#### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	PAINT
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Special Provisions:	163, 223, 367, 955
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	PAINT
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Special Provisions:	A3 A72 A192
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	no
----------------------------	----



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 17 of 18

#### 14.6. Special precautions for user

Combustible liquid. Warning: flammable liquids

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: xylene; 2-methoxy-1-methylethyl acetate

Entry 57: cyclohexane; cyclohexane; cyclohexane; cyclohexane; cyclohexane

2010/75/EU (VOC): 65,908 % (672,259 g/l)

2004/42/EC (VOC): 65,908 % (672,259 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ORALITE® 5018 Screen Printing Ink (080)

Revision date: 11.01.2021

Product code: SDF5018-080N

Page 18 of 18

RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 IMDG: International Maritime Code for Dangerous Goods  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organization

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Naphthenic acids, nickel salts, Reaction mass of 1,2,2,6,6-pentamethyl-4-piperidyl sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*