

Description

This double-sided tape has a special scrim consisting on both sides of a highly transparent, solvent pure acrylate adhesive. This adhesive has an excellent resistance to UV radiation, temperature and moisture. This plasticiser resistant tape has good surface adhesive and cold-flow qualities. The adhesive is lined with a double-sided silicone paper.

Carrier

Special scrim

Liner

White paper, both sides coated with silicone, 90 g/m²

Adhesive

Solvent pure acrylate

Area of use

Mainly for the attachment of skirting boards and decorative mouldings.

Technical Data

Thickness* (adhesive + carrier)	220 micron	
Temperature resistance***	-40° C to +140° C	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	18 N/25 mm
	after 20 min	21 N/25 mm
	after 24 h	25 N/25 mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	18 h	at 23° C
	15 min	at 70° C
Shelf life**	2 years	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.