

Description

This double-sided tape consists of a polyester scrim coated on both sides with a highly transparent acrylic adhesive. The adhesive has excellent resistance to UV radiation, temperature, moisture and plasticisers, as well as good surface adhesion and cold-flow properties.

Carrier

Polyester scrim (blue)

Liner

Double-sided siliconised paper (90 g/m², white)

Adhesive

Pure acrylic

Area of use

This tape is suitable for industrial and commercial applications and is mainly used for the attachment of skirting boards and decorative mouldings.

Technical Data

Thickness* (adhesive + carrier)	220 micron	
Temperature resistance***	-40° C to +140° C	
Adhesion* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	18 N/25 mm
	after 20 min	21 N/25 mm
	after 24 h	25 N/25 mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	18 h	at 23° C
	15 min	at 70° C
Shelf life**	2 years	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.