

Description

This double-sided tape consists of a paper tissue carrier, layered on both sides with a modified dispersion acrylate adhesive. It has a good shear strength and is resistant to ageing and high temperatures. Despite of its strong adhesive qualities it is broad plasticiser resistant. The adhesive is lined with a double-sided silicone paper.

Carrier

Paper tissue, 12,7 g/m²

Liner

Brown paper, silicone-coated on both sides, 90 g/m²

Adhesive

Modified dispersion acrylate

Area of use

This tape is especially suitable for the adhesion of flat surfaces such as metal, polystyrene and paper, as well as hard and soft PVC and trims.

Technical Data

Thickness* (adhesive + carrier)	130 micron	
Temperature resistance***	-40° C to +140° C	
LoopTack* (FINAT TM 9)	18 N/25 mm	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	16 N/25 mm	after 1min
	18 N/25 mm	after 20min
	22 N/25 mm	after 24h
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	72 hours	at 23° C
	5 minutes	at 70° C
Temperature resistance* (S.A.F.T.)	110° C	
Shelf life**	2 years	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.

