

Description

This transfer tape consists of an acrylic adhesive with an excellent resistance to ultraviolet radiation, extreme temperatures, chemicals, solvents and humidity. Its high shear performance provides extremely durable bonds to metal, varnish and high energy plastics surfaces and is durable on low energy surfaces, too.

Carrier

none

Liner

Double-sided siliconised paper (90 g/m², brown)

Adhesive

Modified acrylic, glass fibre filled

Area of use

Ideal as an adhesive medium for foams and materials that require an extremely high shear and adhesive strength as well as temperature resistance in business and industrial applications. It is also appropriate for bonding to lightly structured or stamped surfaces respectively with high initial adhesion. If applied a smallest possible roll angle is recommended.

Technical Data

Thickness* (adhesive without liner)	50 micron	
Temperature resistance***	-40° C to +150° C, momentary up to +190° C	
Resistance to solvents and chemicals	with expert application resistant to most mineral oils, fuels, greases, aliphatic solvents, weak acids, salts and alkalis	
LoopTack* (FINAT TM 9)	20 N/25 mm	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	18 N/25 mm	after 1 min
	22 N/25 mm	after 20 min
	27 N/25 mm	after 24 h
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 400 h	at 23° C
	> 6 h	at 70° C
Temperature resistance* (S.A.F.T.)	150° C	
Shelf life**	2 years	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.

