

## Description

This tape consists of a rayon carrier coated with a rubber adhesive on one side which provides immediate adhesion and good adhesion power over the time.

## Carrier

Rayon, white, black and coloured

## Adhesive

Rubber, transparent

## Area of use

This rip resistant tape can be used for packing, bundling, covering, protection, marking and closing.

## Technical Data

<b>Thickness*</b> (adhesive + carrier)	225 micron	
<b>Temperature resistance***</b>	up to +70° C	
<b>Adhesion*</b> (FINAT TM 1, on stainless steel)	after 1 min	10 N/25 mm
	after 20 min	11 N/25 mm
	after 24 h	12 N/25 mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel)	24 h	at 23° C
<b>Shelf life**</b>	1 year	
<b>Application temperature</b>	> +15° C	

\* average    \*\* in original packaging, at 20°C and 50% relative humidity    \*\*\* 1h, normal climate of Central Europe

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.